

RMR CUT SLIDE FOR GLOCK® 19 GEN 3 - BROWNELLS RMR SLIDE +WINDOW FOR GEN3 GLOCK® 19 STAINLESS NITRIDE

[Handgun Parts](#) > [Slide Parts](#) > [Slides](#)

Integral Red Dot Sight Mounting Slot, Plus a Ton of Custom Features!

The limited production Brownells Brown RMR Slide for Glock® 19 Gen3 pistols features a pre-cut slot for easy, secure, low-profile mounting of a Trijicon RMR or Holosun red dot sight. Up front, there are distinctive, cocking serrations that aid in manipulating the slide to check the chamber or clear a jam. And we'll admit it: the serrations just look cool, too. All RMR Slides also have standard Glock® factory front and rear sight dovetails for "iron" sights. To get proper co-witnessing with the RMR, you will need to also install suppressor-height iron sights. These limited production Brownells Brown slides for the Glock® 19 Gen3 come with a "window" cutout on top between the front serrations that enhances airflow to keep the barrel cooler - ideal for hard-working action competition pistols. Plus, if you have an upgraded barrel with a contrasting finish or a unique exterior pattern (fluting, spirals, "flames," etc.) the window lets you show it off a bit! A Brownells RMR Slide is the ideal upgrade for your factory Glock® 19 Gen3 OR the perfect "top half" for a brand-new custom gun built on a Polymer80 80% frame. Fits Gen3 Glock® 19 pistols & clones Built-in Trijicon RMR mounting slot Also accepts Holosun HE508T, HS507C & HS407C red dot sights Factory front/rear iron sight cuts, too Machined from corrosion-resistant 17-4 stainless steel billet Each RMR Slide for Glock® starts life as a billet of 17-4 stainless steel that is machined to Glock® factory specifications inside, so it'll accept factory or aftermarket barrels and internal parts. Each slide is heat-treated to Rc 41-44 on the Rockwell C scale for added surface hardness and wear resistance. The Brownells Brown slide is a limited production and once they are gone, they're gone. Brownells Gun Tech™ Note: Channel liner required for these slides. Channel liner is a press fit and requires a tool to install. We recommend #777-100-017. Includes patented optic cut technology pioneered by ZEV Technologies. Patent No. RE47335



Attributes

- Name: [BROWNELLS RMR SLIDE +WINDOW FOR GEN3 GLOCK® 19 STAINLESS NITRIDE](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 078200004
- Mfr. No.:
- Cartridge: 9 mm Luger
- Finish: Stainless w/Nitride Finish
- Model: 19
- Sights: RMR
- Style: Window
- Weapon type: Glock
- Delivery weight: 0.292kg
- Shipping height: 51mm
- Shipping width: 140mm
- Shipping length: 279mm
- UPC: 050806112681

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- Startpage
- Safety Instruction Guide for RMR CUT SLIDE FOR GLOCK® 19 GEN 3
- About Us

Safety Instruction Guide for RMR CUT SLIDE FOR GLOCK® 19 GEN 3

Introduction

Thank you for choosing the RMR Cut Slide for Glock® 19 Gen 3 from Brownells. This guide provides essential safety instructions and information to ensure the safe use and installation of your new product. Please read this guide carefully before using or installing the slide.

General Safety Guidelines

- Ensure that the slide is compatible with your Glock® 19 Gen 3 model.
- Always handle firearms and their components with care. Treat every firearm as if it is loaded.
- Keep the slide and all firearm components out of reach of children and unauthorized individuals.
- Use only factory or compatible aftermarket parts for installation to avoid potential hazards.
- Regularly inspect the slide and firearm for any signs of wear or damage.
- Follow all local laws and regulations regarding firearm modifications and usage.

Specific Safety Precautions for Use

- **Cocking Serrations:** The distinctive cocking serrations are designed to aid in manipulating the slide. Always ensure a secure grip to prevent slips during operation.
- **Optic Installation:** When mounting a Trijicon RMR or Holosun red dot sight, follow the manufacturer's instructions carefully to ensure proper installation.
- **Iron Sights:** For proper cowitnessing with the RMR, install suppressorheight iron sights. Ensure that these sights are compatible with the slide.
- **Heat Management:** The window cutout enhances airflow to keep the barrel cooler. However, always allow the firearm to cool down after extensive use to prevent overheating.
- **Channel Liner:** A channel liner is required for these slides. Ensure you use the recommended tool for installation to avoid damage.

Instructions for Installation and Usage

1. Preparation:

- Ensure the firearm is unloaded and pointed in a safe direction.
- Gather necessary tools, including the recommended channel liner installation tool (#777100017).

2. Installation Steps:

- Remove the factory slide from your Glock® 19 Gen 3.
- Install the channel liner into the new RMR slide using the recommended tool.
- Align the slide with the frame and ensure it fits securely.
- Mount the Trijicon RMR or Holosun red dot sight according to the manufacturer's instructions.
- Install suppressorheight iron sights if cowitnessing is desired.

3. Usage:

- Regularly check that all components are secure before use.
- Practice safe handling and storage of your firearm at all times.

Disposal Instructions

- Dispose of the RMR slide and any packaging materials in accordance with local regulations.
- Do not dispose of any firearm components in regular household waste. Check for specific disposal guidelines in your area.

Contact Information for Further Support

For any safety inquiries or additional support regarding this product, please refer to the manufacturer's contact details provided with your purchase.

By following these guidelines, you can ensure safe and effective use of your RMR Cut Slide for Glock® 19 Gen 3. Always prioritize safety and stay informed about best practices for firearm handling and maintenance.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk