

BLACK FRONT SIGHTS FOR GLOCK .125" HEIGHT - Black Serrated, .245 x .125

"Working" Sights For Duty, Carry, Or Competition; Fiber Optic & Tritium Options

Used by numerous IDPA and USPSA National champions, as well as law enforcement professionals, these streamlined, steel sights are built for fast target acquisition. Ramped Front Sights are available with a black, serrated rear face to minimize glare.



Attributes

- Name: [Black Serrated, .245 x .125](#)
- Manufacturer: [WARREN TACTICAL SERIES](#)
- Product no.: 100005080
- Mfr. No.: GLOCKWTLO
- Color: Black
- Height: .245
- Make: Glock
- Outline: None
- Style: Plain,Serrated
- Width: .125
- Delivery weight: 0.005kg
- Shipping height: 1mm
- Shipping width: 83mm
- Shipping length: 146mm

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for BLACK FRONT SIGHTS FOR GLOCK .125" HEIGHT](#)
- [About Us](#)

Safety Instruction Guide for BLACK FRONT SIGHTS FOR GLOCK .125" HEIGHT

Introduction

Thank you for choosing the BLACK FRONT SIGHTS FOR GLOCK .125" HEIGHT. This guide provides essential safety instructions to ensure the safe use and installation of your product. Please read this document carefully before using the sights to understand the safety precautions and proper handling.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Always follow local laws and regulations regarding firearm accessories.
- Inspect the product for any visible damage or defects before installation.
- Store the product in a safe place, away from children and unauthorized users.
- Report any unsafe product experiences or accidents to relevant authorities.
- Check the EU's Safety Gate platform regularly for recall updates.

Specific Safety Precautions for Use

- Use only with Glock firearms as specified.
- Avoid using the sights in extreme weather conditions that could affect visibility or performance.
- Ensure that the firearm is unloaded when installing or adjusting the sights.
- Do not attempt to modify the sights; any alterations can compromise safety and performance.
- If you experience any issues with the sights, discontinue use immediately and seek professional assistance.

Instructions for Installation and Usage

1. Preparation

- Gather necessary tools: a small screwdriver and a torque wrench (if applicable).
- Ensure the firearm is unloaded and pointed in a safe direction.

2. Installation Steps

- Remove the existing front sight from your Glock using the appropriate tool.
- Align the new BLACK FRONT SIGHT with the sight dovetail on the slide.
- Gently tap the sight into place using a nonmarring tool to avoid damage.
- Ensure the sight is securely fitted and does not move.

3. Adjustment

- If necessary, make any adjustments to align the sight for optimal accuracy.
- Test the alignment by aiming at a target and making minor adjustments as needed.

4. Usage

- Familiarize yourself with the sight's function before engaging in live fire.
- Practice in a safe environment to ensure comfort and proficiency with the new sights.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling options for metal components if applicable.

Contact Information for Further Support

For any inquiries or assistance regarding the BLACK FRONT SIGHTS, please consult your retailer or manufacturer's website for support resources.

By following these safety guidelines, you can ensure a safe and effective experience with your BLACK FRONT SIGHTS FOR GLOCK .125" HEIGHT. Thank you for your attention to safety!

About Us

Brownells Česká republika

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.cz