

ROCKSETT ALL-PURPOSE CERAMIC ADHESIVE - FLEXBAR

ROCKSETT ALL-PURPOSE CERAMIC ADHESIVE 2OZ

[Gunsmith Tools](#) > [General Gunsmith Tools](#) > [Thread Locking Liquids](#)

ROCKSETT ALL-PURPOSE CERAMIC ADHESIVE The FLEXBAR Rocksett is a high-temperature ceramic adhesive cement designed for securing threaded and cylindrical assemblies, such as flash hiders and muzzle brakes. It offers exceptional temperature resistance, withstanding ranges from -350°F up to 2,015°F, making it ideal for applications involving extreme heat. Rocksett acts as a vibration-dampening material, ensuring components remain secure under dynamic conditions. This non-toxic, odorless, and non-flammable adhesive is resistant to oils, fuels, acids, and alkalis, providing a durable bond without the need for mixing or priming. Its long shelf life and ability to bond materials like ceramic, glass, and metals make it a versatile choice for various applications.

Key Features: Temperature Resistance: Withstands temperatures from -350°F to 2,015°F. Vibration Dampening: Secures components against movement and loosening. Chemical Resistance: Resistant to oils, fuels, acids, and alkalis. User-Friendly: Non-toxic, odorless, non-flammable, and requires no mixing or priming. Specifications: Container Size: 2 oz. bottle. Application: Ideal for bonding ceramic, glass, and metals; commonly used for attaching muzzle devices. Customer Insights: Users have expressed high satisfaction with the FLEXBAR Rocksett, noting its effectiveness in securing muzzle devices and its resilience under high-temperature conditions. The product has received a high rating, reflecting its reliability and performance in various applications.

Incorporating FLEXBAR Rocksett into your assembly processes ensures durable and dependable bonding of components exposed to extreme temperatures and vibrations, enhancing the longevity and performance of your equipment.



Attributes

- Name: [FLEXBAR ROCKSETT ALL-PURPOSE CERAMIC ADHESIVE 2OZ](#)
- Manufacturer: [FLEXBAR](#)
- Product no.: 100010681
- Mfr. No.: 15014
- Colour: Clear
- Size: 2 oz
- Delivery weight: 0.113kg
- Shipping height: 46mm
- Shipping width: 46mm
- Shipping length: 157mm
- UPC: 608060400268

Table of Contents

- Startpage
- ROCKSETT ALLPURPOSE CERAMIC ADHESIVE SAFETY INSTRUCTIONS
- About Us

ROCKSETT ALLPURPOSE CERAMIC ADHESIVE SAFETY INSTRUCTIONS

Introduction

Thank you for choosing ROCKSETT ALLPURPOSE CERAMIC ADHESIVE. This guide provides essential safety instructions to ensure the safe and effective use of this product. Please read this manual carefully before using the adhesive to understand the potential hazards and necessary precautions.

General Safety Guidelines

- Always use ROCKSETT in a wellventilated area to avoid inhalation of fumes.
- Keep the product out of reach of children and pets.
- Wear appropriate personal protective equipment (PPE), such as gloves and safety goggles, when handling the adhesive.
- Do not use the adhesive for any purpose other than its intended use.
- If you experience any adverse reactions, discontinue use immediately and seek medical advice.

Specific Safety Precautions for Use

- **Temperature Awareness:** Ensure that the surfaces to be bonded are at a temperature within the adhesive's operational range (350°F to 2,015°F).
- **Surface Preparation:** Clean surfaces thoroughly to remove any dust, oil, or contaminants that may interfere with adhesion.
- **Application Method:** Apply the adhesive in a wellventilated area, using a suitable applicator to avoid direct contact with skin.
- **Storage:** Store the adhesive in a cool, dry place away from direct sunlight and heat sources.
- **Disposal:** Dispose of any unused adhesive and containers according to local regulations for hazardous waste.

Instructions for Installation and Usage

1. Preparation:

- Ensure the surfaces to be bonded are clean, dry, and free from contaminants.
- Shake the adhesive bottle well before use.

2. Application:

- Squeeze a small amount of the adhesive onto one of the surfaces to be bonded.
- Press the surfaces together firmly and hold for a few seconds to ensure a good bond.
- Allow the adhesive to cure as per the manufacturer's recommendations.

3. Curing Time:

- Allow adequate time for the adhesive to cure fully before subjecting the bonded surfaces to stress or load.

4. Cleaning Up:

- Clean any excess adhesive immediately with a suitable solvent.
- Wash hands thoroughly after handling the adhesive.

Disposal Instructions

- Dispose of the adhesive container and any leftover product in accordance with local regulations for hazardous materials.
- Do not pour adhesive down the drain or throw it in regular trash.

Contact Information for Further Support

For any safety inquiries or additional information regarding the use of ROCKSETT ALLPURPOSE CERAMIC ADHESIVE, please refer to the product packaging or visit the manufacturer's website.

Conclusion

By following these safety instructions, you can ensure the safe and effective use of ROCKSETT ALLPURPOSE CERAMIC ADHESIVE. Always prioritize safety and do not hesitate to seek assistance if needed. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk