

1913 PICATINNY RAIL - ACCU-SHOT PICATINNY RAIL ADAPTER 3.35" BLACK

[Shooting Accessories](#) > [Bipods, Monopods & Accessories](#) > [Bipod Accessories](#)

ATLAS BIPOD 1913 PICATINNY RAIL Atlas 1913 Rails serve as attachment points for Atlas Bipods that fit Picatinny rails. 3.35" rail accommodates hole patterns with 1.76" to 2.78" center-to-center spacing and fits onto curved surfaces. 4" rail accommodates hole patterns with 2.2" to 3.5" center-to-center spacing and fits onto flat surfaces. Rails attach to the stock with either a sling stud and spacer or machine screws, (not included).



Attributes

- Name: [ACCU-SHOT PICATINNY RAIL ADAPTER 3.35" BLACK](#)
- Manufacturer: [ACCU-SHOT](#)
- Product no.: 100012057
- Mfr. No.: BT15
- Application: Picatinny Rail Mount
- Attachment: Handguard
- Delivery weight: 0.023kg
- Shipping height: 20mm
- Shipping width: 94mm
- Shipping length: 206mm
- UPC: 810040220234

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [1913 PICATINNY RAIL ACCUSHOT PICATINNY RAIL ADAPTER Safety Instructions](#)
- [About Us](#)

1913 PICATINNY RAIL ACCUSHOT PICATINNY RAIL ADAPTER Safety Instructions

Introduction

Thank you for choosing the 1913 PICATINNY RAIL ACCUSHOT PICATINNY RAIL ADAPTER. This product is designed to provide a stable attachment point for your Atlas Bipod, enhancing your shooting experience. To ensure safe and effective use of this product, please read and follow the instructions and safety guidelines outlined in this document.

General Safety Guidelines

- Always ensure that the product is installed correctly before use.
- Regularly inspect the rail and attachment points for any signs of wear or damage.
- Use the product only as intended, following all guidelines for installation and usage.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe products or accidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure the rail is securely attached to the handguard before mounting the bipod.
- Use only compatible bipods with Picatinny rails to avoid accidents.
- Do not exceed the recommended weight limit for the bipod attachment.
- Avoid using the bipod on unstable or uneven surfaces.
- Do not modify the rail or its components in any way.

Instructions for Installation and Usage

1. Installation

- Identify the mounting location on your handguard where the rail will be attached.
- Ensure the surface is clean and free of debris.
- Choose the appropriate attachment method:
 - For curved surfaces, use the sling stud and spacer (not included).
 - For flat surfaces, use machine screws (not included).
- Align the rail with the desired hole pattern, ensuring the centertocenter spacing matches (1.76" to 2.78" for the 3.35" rail).
- Securely fasten the rail in place, ensuring it does not move or wobble.

2. Usage

- Once installed, attach your Atlas Bipod to the rail following the manufacturer's instructions.
- Always check the stability of the bipod before use.
- Adjust the bipod legs as necessary for optimal positioning.
- After use, detach the bipod and store the rail in a safe location.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- If the product is damaged or no longer in use, consider recycling materials where possible.

Contact Information for Further Support

For any safety inquiries or additional support regarding the 1913 PICATINNY RAIL ACCUSHOT PICATINNY RAIL ADAPTER, please contact the manufacturer directly. Ensure you have your product details ready for reference.

Thank you for your attention to these safety instructions. By following these guidelines, you can ensure a safe and enjoyable experience with your product.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk