


MATCH 22 CALIBER (0.224") HOLLOW POINT BOAT TAIL BULLETS - MATCH .22 CALIBER (0.224") 75GR BTHP 4,000/BOX

[Reloading](#) > [Bullets](#) > [Rifle Bullets](#)

Hornady 22 Caliber (0.224") are built with a rugged AMP® bullet jacket (Advanced Manufacturing Process) that clearly delivers better performance. The thin-plated full metal jacket offered by other manufacturers is easily distorted and often breaks or separates when the bullet impacts the target. The Hornady AMP bullet jacket features virtually zero tolerance for concentricity and near-zero wall thickness variation, punching through targets without deforming or breaking.



Attributes

- Name: [MATCH .22 CALIBER \(0.224"\) 75GR BTHP 4,000/BOX](#)
- Manufacturer: [HORNADY](#)
- Product no.: 100018875
- Mfr. No.: 2279B
- Ballistic Coefficient (G1): 0.395
- Brand Style: Match
- Bullet Style: Hollow Point Boat Tail (HPBT)
- Caliber: 22 Caliber
- Diameter (Breech): -
- Diameter (in): 0.224
- Grain: 75
- Sectional Density: 0.214
- Quantity: 4,000
- Delivery weight: 19.958kg
- Shipping height: 83mm
- Shipping width: 229mm
- Shipping length: 305mm
- UPC: 090255690507

Item details

Made in USA

US export classification: 0A505.x

Table of Contents

- [Startpage](#)
- [MATCH 22 CALIBER \(0.224"\) HOLLOW POINT BOAT TAIL BULLETS SAFETY INSTRUCTIONS](#)
- [About Us](#)

MATCH 22 CALIBER (0.224") HOLLOW POINT BOAT TAIL BULLETS SAFETY INSTRUCTIONS

Introduction

Thank you for choosing Hornady MATCH 22 CALIBER (0.224") HOLLOW POINT BOAT TAIL BULLETS. This guide provides essential safety instructions to ensure safe handling, usage, and disposal of this product in compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure that all users are aware of and understand the safety instructions before using the product.
- Always handle ammunition with care and respect.
- Store the product in a secure location, out of reach of children and unauthorized users.
- Regularly check for any product recalls or safety alerts on the EU's Safety Gate platform.
- Report any unsafe products or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Always wear appropriate safety gear, including eye and ear protection, when using this product.
- Ensure that the firearm is in good working condition and compatible with the .22 caliber ammunition.
- Do not use damaged or altered bullets.
- Avoid exposing the ammunition to extreme temperatures or humidity.
- Keep ammunition away from open flames or sparks.
- Do not mix different brands or types of ammunition.

Instructions for Installation and Usage

1. Installation:

- Ensure the firearm is unloaded before handling any ammunition.
- Carefully insert the bullet into the chamber of the firearm as per the manufacturer's instructions.

2. Usage:

- Always point the firearm in a safe direction.
- Keep your finger off the trigger until you are ready to shoot.
- Be aware of your surroundings and ensure that the area is clear of people and obstacles before firing.
- Follow all local laws and regulations regarding the use of firearms and ammunition.

Disposal Instructions

- Dispose of any unused or expired ammunition in accordance with local regulations.
- Do not throw ammunition in regular trash or burn it.
- Contact local authorities or waste management services for proper disposal methods.

Contact Information for Further Support

For any inquiries regarding safety or product information, please refer to the official Hornady website or contact their customer service directly. Ensure you have your product details ready for a swift response.

By following these safety instructions, you can ensure a safe and enjoyable experience with your Hornady

MATCH 22 CALIBER (0.224") HOLLOW POINT BOAT TAIL BULLETS. Always prioritize safety and comply with all relevant regulations. Thank you for your attention to these important guidelines.

About Us

Brownells Česká republika

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.cz