

SIG P238/P938 LASERGUARD - SIG P238/P938 GREEN LASERGUARD®

[Optics & Mounting](#) > [Electronic Sights](#) > [Laser Sights](#)

Sig Sauer fans wanted a compact, lightweight pistol that performed like a full size. Enter the P238 in .380 and the P938 in 9mm. To enhance targeting acquisition of this fine shooting compact, Crimson Trace's LG-492G Laserguard® attaches to the trigger guard of the P238/P938 by two factory supplied screws. The LG-492G is fully adjustable for windage and elevation and comes sighted in at 50 feet from the factory. See our holsters section for a custom holster to securely fit your laser equipped P238 or P938.



Attributes

- Name: [SIG P238/P938 GREEN LASERGUARD®](#)
- Manufacturer: [CRIMSON TRACE CORPORATION](#)
- Product no.: 100019535
- Mfr. No.: LG-492G
- Battery: 1/3N Lithium,357
- Color: Black
- Laser Color: Green
- Material: Polymer
- Style: Laserguard
- Delivery weight: 0.102kg
- Shipping height: 57mm
- Shipping width: 83mm
- Shipping length: 140mm
- UPC: 610242006656

Item details

Made in USA

This product contains a battery.

Table of Contents

- [Startpage](#)
- [SIG P238/P938 LASERGUARD Safety Instructions](#)
- [About Us](#)

SIG P238/P938 LASERGUARD Safety Instructions

Introduction

Thank you for choosing the SIG P238/P938 LASERGUARD. This guide provides essential safety instructions to ensure the safe use of your laser sight. It is crucial to understand the guidelines and precautions to enhance your experience while maintaining safety.

General Safety Guidelines

- Always treat the firearm as if it is loaded.
- Keep the laser sight out of reach of children and unauthorized users.
- Do not point the laser at anyone, including yourself, or at reflective surfaces.
- Ensure that the laser is used in accordance with local laws and regulations.
- Regularly inspect the laser sight for any signs of damage or malfunction before use.
- Store the laser sight in a secure location when not in use.

Specific Safety Precautions for Use

- Always wear appropriate eye protection when using the laser.
- Do not modify or attempt to repair the laser sight yourself.
- Avoid using the laser in situations where it may cause distraction or panic.
- Be aware of your surroundings and ensure that the laser is not directed towards people or animals.
- Do not use the laser if it is not functioning correctly; seek professional assistance.

Instructions for Installation and Usage

Installation

1. Ensure the firearm is unloaded and pointed in a safe direction.
2. Locate the trigger guard on your SIG P238 or P938.
3. Align the LG492G Laserguard with the trigger guard.
4. Secure the Laserguard using the two factory-supplied screws. Ensure they are tightened adequately but do not overtighten.
5. Check that the Laserguard is firmly attached and does not wobble.

Usage

- To activate the laser, press the activation button located on the Laserguard.
- Adjust the laser for windage and elevation as needed. The laser is factory sighted at 50 feet.
- Regularly check the battery status and replace with a 1/3N Lithium or 357 battery as needed.
- Practice using the laser in a safe environment to become familiar with its operation.

Disposal Instructions

- Dispose of the laser sight in accordance with local regulations regarding electronic waste.
- Remove the battery before disposal and recycle it according to local guidelines.
- Do not dispose of the laser sight in regular household waste.

Contact Information for Further Support

For any questions or concerns regarding the SIG P238/P938 LASERGUARD, please refer to the manufacturer's website or contact their support team for assistance.

Conclusion

Following these safety instructions will help ensure a safe and enjoyable experience with your SIG P238/P938 LASERGUARD. Always prioritize safety and responsibility when handling firearms and laser sights. Thank you for your attention to these important guidelines.

About Us

Brownells Česká republika

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.cz