SAVAGE M12 FTR RND BACK SA F-CLASS 3" EXT PICATINNY SCOPE MOUNT - EGW SAVAGE M12 FTR SA RND REC 1-PC 3" EXT PIC BASE 0MOA SINGLE

Optics & Mounting > Rings, Mounts & Bases > Rifle Bases

This Savage base will work with any short action round back Savage rifle without an ejection port. It has an extra 3"" over the front of the receiver. Savages without an accu-trigger will require our flat back mount (listed separately). EGW recommends measuring the hole spacing in your receiver to confirm it matches with the dimensions they have published. Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The channel in the center reduces the overall mass of the mount. Also, in many cases, it will not obstruct usage of factory iron sights. EGW one-piece scope mounts are the obvious choice for hunters and tactical shooters alike. EGW machines these in their shop using one of their machining centers. After machining, the mounts are tumbled, sand blasted, and Type II anodized for long lasting durability. Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is sold separately). Recommend: 0 MOA - if shooting 0-500 yards The entire mount and accessories (from the mounting screws and wrench down to the packaging) are made in the USA. 41030 Mount Fits: Savage Model 10 Short Action Round Rear Receiver Savage Model 11 Short Action Round Rear Receiver Savage Model 12 Short Action Round Rear Receiver Savage Model 14 Short Action Round Rear Receiver Savage Model 16 Short Action Round Rear Receiver Savage Model 110 Short Action Round Rear Receiver Stevens Model 200 Short Action Round Rear Receiver 41040 mount fits: Savage Model 12 FTR Short Action Round Rear Receiver Please check your mounting screw diameter and hole spacing before placing your order to ensure you select the correct mount.

Attributes

- Name: EGW SAVAGE M12 FTR SA RND REC 1-PC 3" EXT PIC BASE 0MOA SINGLE
- Manufacturer: EGW
- Product no.: 296000439
- Mfr. No.: 41040
- Color: Black
- Elevation: 0 MOA
- Make: Savage,Savage Arms
- Model: F-Class
- Model Number: For Rifle Without Ejection Port
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Delivery weight: 0.127kg
- UPC: 841370105434

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for SAVAGE M12 FTR RND BACK SA FCLASS 3″ EXT PICATINNY SCOPE MOUNT
- About Us

Safety Instruction Guide for SAVAGE M12 FTR RND BACK SA FCLASS 3" EXT PICATINNY SCOPE MOUNT

Introduction

Thank you for choosing the SAVAGE M12 FTR RND BACK SA FCLASS 3" EXT PICATINNY SCOPE MOUNT. This guide is designed to ensure your safety and the proper use of this product. It is important to read and understand the safety instructions outlined in this document before using the mount.

General Safety Guidelines

- Always ensure that the mount is compatible with your firearm model before installation.
- Handle all firearms and accessories with care and follow all safety protocols.
- Keep the mount and all accessories out of reach of children and unauthorized users.
- Regularly inspect the mount for any signs of wear or damage.
- If you experience any issues with the mount, discontinue use and seek assistance.

Specific Safety Precautions for Use

- Ensure that the mount is securely attached to the firearm before use.
- Use only the recommended torque specifications (20 inch lbs) when installing the mount.
- Apply a drip of blue loctite to the mounting screws to ensure a secure fit.
- Avoid using the mount in extreme weather conditions that may affect its performance.
- Do not modify the mount or use it in ways not specified in this guide.

Instructions for Installation and Usage

1. **Preparation:**
    - Gather the necessary tools: a torque wrench and the appropriate mounting screws.
    - Ensure you have a clean, dry workspace to perform the installation.
2. **Measuring:**
    - Measure the hole spacing in your receiver to confirm compatibility with the mount dimensions.
    - Check the mounting screw diameter to ensure it matches the specifications.
3. **Installation:**
    - Align the mount with the holes on the receiver.
    - Insert the mounting screws and handtighten them.
    - Use the torque wrench to tighten the screws to the recommended torque of 20 inch lbs.
    - Apply a drip of blue loctite to the screws for added security.
4. **Final Checks:**
    - Inspect the mount to ensure it is securely attached and does not obstruct the use of factory iron sights.
    - Test the mount by gently pulling on it to ensure it is firmly in place.
5. **Usage:**

    - When mounting your scope, utilize the Picatinny cross slots for flexibility.
    - Ensure that all accessories are securely attached and do not interfere with the operation of the firearm.

Disposal Instructions

- Dispose of the mount and packaging responsibly in accordance with local regulations.
- Do not dispose of the mount in regular household waste if it contains any hazardous materials.
- Consider recycling any metal components if possible.

Contact Information for Further Support

For any questions or concerns regarding the use of the SAVAGE M12 FTR RND BACK SA FCLASS 3" EXT PICATINNY SCOPE MOUNT, please refer to the manufacturer's customer support resources.

Thank you for prioritizing safety and responsible usage. Enjoy your shooting experience!

About Us

Brownells Europe

Brownells Europe - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

P.O.Box 4300
Warwick
CV34 9BR

www.brownells.eu