

# SAVAGE M12 FTR RND BACK SA F-CLASS 3" EXT PICATINNY SCOPE MOUNT - EGW SAVAGE M12 FTR SA RND REC 1-PC 3" EXT PIC BASE 0MOA EJECT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

This Savage base will work with any short action round back Savage rifle without an ejection port. It has an extra 3" over the front of the receiver. Savages without an accu-trigger will require our flat back mount (listed separately). EGW recommends measuring the hole spacing in your receiver to confirm it matches with the dimensions they have published. Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. The channel in the center reduces the overall mass of the mount. Also, in many cases, it will not obstruct usage of factory iron sights. EGW one-piece scope mounts are the obvious choice for hunters and tactical shooters alike. EGW machines these in their shop using one of their machining centers. After machining, the mounts are tumbled, sand blasted, and Type II anodized for long lasting durability. Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is sold separately). Recommend: 0 MOA - if shooting 0-500 yards The entire mount and accessories (from the mounting screws and wrench down to the packaging) are made in the USA. 41030 Mount Fits: Savage Model 10 Short Action Round Rear Receiver Savage Model 11 Short Action Round Rear Receiver Savage Model 12 Short Action Round Rear Receiver Savage Model 14 Short Action Round Rear Receiver Savage Model 16 Short Action Round Rear Receiver Savage Model 110 Short Action Round Rear Receiver Stevens Model 200 Short Action Round Rear Receiver 41040 mount fits: Savage Model 12 FTR Short Action Round Rear Receiver Please check your mounting screw diameter and hole spacing before placing your order to ensure you select the correct mount.



## Attributes

- Name: [EGW SAVAGE M12 FTR SA RND REC 1-PC 3" EXT PIC BASE 0MOA EJECT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000440
- Mfr. No.: 41030
- Color: Black
- Elevation: 0 MOA
- Make: Savage,Savage Arms
- Model: F-Class
- Model Number: For Rifle With Ejection Port
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Delivery weight: 0.097kg
- UPC: 841370105427

## Item details

Made in USA

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for SAVAGE M12 FTR RND BACK SA FCLASS 3" EXT PICATINNY SCOPE MOUNT](#)
- [About Us](#)

# Safety Instruction Guide for SAVAGE M12 FTR RND BACK SA FCLASS 3" EXT PICATINNY SCOPE MOUNT

## Introduction

Thank you for choosing the SAVAGE M12 FTR RND BACK SA FCLASS 3" EXT PICATINNY SCOPE MOUNT manufactured by EGW. This guide provides essential safety instructions and guidelines to ensure the safe use and installation of your scope mount. Please read this document carefully to familiarize yourself with the product and its safe handling.

## General Safety Guidelines

- Ensure that the scope mount is compatible with your specific Savage rifle model.
- Always handle firearms and accessories with care and in accordance with standard safety practices.
- Keep the product out of reach of children and unauthorized users.
- Regularly inspect the scope mount for any signs of wear or damage.
- Do not modify the scope mount or use it in a manner not intended by the manufacturer.
- Report any unsafe products or accidents to the relevant authorities.
- Check for recall updates on the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- Ensure that the mounting screws are tightened to the recommended torque of 20 inch lbs.
- Use a drip of blue Loctite on the screws to prevent loosening during use (Loctite is sold separately).
- Be cautious when using the mount with factory iron sights; ensure that they are not obstructed.
- Avoid using the mount in extreme conditions that may compromise its integrity.
- If you are unsure about the installation or usage, seek assistance from a qualified professional.

## Instructions for Installation and Usage

### 1. Preparation

- Gather all necessary tools, including a torque wrench and the appropriate mounting screws.
- Ensure that your Savage rifle is unloaded and pointed in a safe direction during installation.

### 2. Measuring

- Before installation, measure the hole spacing in your receiver to ensure it matches the dimensions provided by EGW.

### 3. Installation Steps

- Align the scope mount with the receiver of your rifle.
- Insert the mounting screws through the holes in the mount and into the receiver.
- Tighten the screws gradually, ensuring even pressure across the mount.
- Use a torque wrench to tighten the screws to the specified torque of 20 inch lbs.
- Apply a small amount of blue Loctite to the screws to secure them.

### 4. Final Checks

- Verify that the mount is securely attached to the rifle.

- Check that the Picatinny cross slots are free from debris and ready for mounting scope rings and accessories.

## 5. Usage

- Once installed, you may proceed to mount your scope and other accessories according to your preferences.
- Regularly check the mount and screws for tightness and integrity during use.

## Disposal Instructions

- Dispose of the packaging materials in accordance with local recycling regulations.
- If the product is no longer in use, dispose of it in a manner that complies with local waste management guidelines.
- Do not dispose of the product in fire or water, as it may release harmful substances.

## Contact Information for Further Support

For any inquiries or concerns regarding the safety and usage of the SAVAGE M12 FTR RND BACK SA FCLASS 3" EXT PICATINNY SCOPE MOUNT, please refer to the manufacturer's contact information provided with your product packaging or visit their official website for support.

Thank you for prioritizing safety and responsible usage of your new scope mount. Enjoy your shooting experience with the SAVAGE M12 FTR!

# About Us

## Brownells Europe

**Brownells Europe - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

P.O.Box 4300  
Warwick  
CV34 9BR

[www.brownells.eu](http://www.brownells.eu)