

S&W M&P TRIJICON RMR SIGHT MOUNT - EGW S&W M&P TRIJICON RMR SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.780
Overall Width: 1.1" Mounting Hardware: (2) 6-32 Flat Head Screws, (1) 6-32 X 3/16 Set Screw Red Dot Fitment: Trijicon RMR This mount will fit: Smith & Wesson M&P Full Size Smith & Wesson M&P 2.0 Full Size Smith & Wesson M&P 22 Full Size Smith & Wesson M&P Compact* Smith & Wesson M&P 2.0 Compact* Smith & Wesson SD9VE Smith & Wesson SD40VE This mount does not fit: Smith & Wesson M&P Shield (Our mount is too wide to fit the Shield) Smith & Wesson M&P Shield EZ .380 Smith & Wesson SW9VE Smith & Wesson SW40VE Smith & Wesson M&P C.O.R.E Series *Will not fit the M&P .22 Compact. Smith and Wesson's rear sight dovetails are known to vary in dimensions. Our sights are made to the same tolerances. Some users may have trouble installing our plate on their slide due to the varying tolerances in your slides. Please keep this in mind when ordering. These mounts should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs *Rear sight pusher tool highly recommended*



Attributes

- Name: [EGW S&W M&P TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000567
- Mfr. No.: 49508
- Colour: Black
- Material: Aluminum
- Model: M&P 2.0 Compact,M&P 22,M&P Compact
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Smith & Wesson
- Delivery weight: 0.033kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 127mm
- UPC: 841370116812

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for S&W M&P Trijicon RMR Sight Mount
- About Us

Safety Instruction Guide for S&W M&P Trijicon RMR Sight Mount

Introduction

Thank you for choosing the S&W M&P Trijicon RMR Sight Mount. This guide provides important safety instructions and installation information to ensure the safe and effective use of the product. Please read this guide thoroughly before use.

General Safety Guidelines

- Always handle firearms and accessories with care and follow all safety protocols.
- Ensure that the sight mount is compatible with your specific firearm model before installation.
- Inspect the product for any visible damage or defects before use.
- Keep the product out of reach of children and unauthorized users.
- If you are unsure about the installation or usage, consult a qualified gunsmith.

Specific Safety Precautions for Use

- This mount is designed specifically for the following models:
 - Smith & Wesson M&P Full Size
 - Smith & Wesson M&P 2.0 Full Size
 - Smith & Wesson M&P 22 Full Size
 - Smith & Wesson M&P Compact
 - Smith & Wesson M&P 2.0 Compact
 - Smith & Wesson SD9VE
 - Smith & Wesson SD40VE
- The mount does not fit the following models:
 - Smith & Wesson M&P Shield
 - Smith & Wesson M&P Shield EZ .380
 - Smith & Wesson SW9VE
 - Smith & Wesson SW40VE
 - Smith & Wesson M&P C.O.R.E Series
- Ensure that the rear sight dovetail dimensions of your firearm match the mount specifications. Variations in dimensions may affect installation.
- Use a rear sight pusher tool for installation to avoid damaging the firearm or the mount.
- Always use the provided mounting hardware and apply blue Loctite to the screws to prevent loosening during use.
- Torque the mounting screws to 15 in/lbs to ensure secure installation.

Instructions for Installation and Usage

1. Remove the rear sight from your firearm.
2. Install the EGW Sight Mount into the dovetail of your firearm.
3. Tighten the set screw (if applicable) to secure the mount.
4. Place the red dot sight on the EGW Sight Mount. To make removal easier, place a small piece of paper between the red dot sight and the sight mount to prevent Loctite from adhering to the sight.
5. Apply blue Loctite to the provided mounting screws.
6. Torque the mounting screws to 15 in/lbs.
7. Ensure everything is secure before using the firearm.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- Consider recycling options if available.

Contact Information for Further Support

For further assistance regarding safety inquiries or product support, please contact your local authorized dealer or manufacturer. Ensure you have the product details available for a more efficient service.

Please keep this guide for future reference and ensure all users of the product are aware of the safety instructions provided. Thank you for prioritizing safety with your S&W M&P Trijicon RMR Sight Mount.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk