

WALTHER PPQ TRIJICON RMR SIGHT MOUNT - EGW WALTHER PPQ TRIJICON RMR SIGHT MOUNT

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

Material: 7075 Aluminum Coating: Matte Black Hardcoat Overall Length: 1.78" Overall Width: 1.1" Mounting Hardware: (2) 8-32 Button Head Screws, (1) 8-32 Set Screw) Red Dot Fitment: Trijicon RMR, Holosun HS507C This mount fits: Walther PPQ Classic (M1) Walther PPQ M2 (All Models) Walther PPQ 45 Walther PPQ 45 SD Walther PPQ Sub Compact Walther P99 (All Models) Walther PPX (All Models) Walther Creed Walther Creed 10 Round Walther PPS (All Models) Walther PPS M2 (All Models) This mount does not fit: Walther PPQ 22 Walther PPQ Q4 Tac Walther Q5 Match Simply remove the rear sight on your gun and replace it with our mount in order to mount your Trijicon RMR red-dot sight. No alterations are required. You can take our mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions

Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs The screws that are included with this mount require a 5/64" allen wrench for installation.



Attributes

- Name: [EGW WALTHER PPQ TRIJICON RMR SIGHT MOUNT](#)
- Manufacturer: [EGW](#)
- Product no.: 296000595
- Mfr. No.: 49536
- Colour: Black
- Material: Aluminum
- Model: P99,PPQ,PPQ M2,PPS,PPS M2,PPX
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Walther
- Delivery weight: 0.032kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 127mm
- UPC: 841370116874

Item details

Made in USA

Table of Contents

- Startpage
- [WALTHER PPQ TRIJICON RMR SIGHT MOUNT Safety Instructions](#)
- About Us

WALTHER PPQ TRIJICON RMR SIGHT MOUNT Safety Instructions

Introduction

Thank you for choosing the WALTHER PPQ TRIJICON RMR SIGHT MOUNT. This product is designed to enhance your shooting experience by allowing you to mount a Trijicon RMR red dot sight on your Walther handgun. Please read this safety instruction guide carefully to ensure safe and proper use of the product in compliance with EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Always handle firearms responsibly and in accordance with local laws and regulations.
- Keep the product out of reach of children and vulnerable individuals.
- Inspect the mount and your firearm regularly for any signs of wear or damage.
- Report any unsafe products or accidents to the relevant authorities.
- Stay informed about product recalls through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Hazard Identification:** Improper installation may result in the sight becoming loose or detaching, which could lead to accidents. Failure to use the correct tools may damage the mounting hardware or the firearm.
- **Avoiding Hazards:** Always ensure that the firearm is unloaded before installation or maintenance. Use the provided mounting hardware as specified; do not substitute with other screws or tools. Follow all installation instructions carefully to ensure proper fit and function.
- **Age Specific Warnings:** This product is intended for use by individuals who are legally permitted to handle firearms. Ensure that users are of legal age and have appropriate training.

Instructions for Installation and Usage

1. Preparation:

- Ensure that your firearm is unloaded.
- Gather the necessary tools, including a 5/64" allen wrench.

2. Installation Steps:

- Remove the rear sight from your Walther handgun.
- Install the EGW Sight Mount in the dovetail where the rear sight was located.
- Tighten the set screw (if applicable) to secure the mount.
- Place the Trijicon RMR red dot sight on the EGW Sight Mount.
 - Note: Placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.
- Apply blue Loctite to the provided mounting screws.
- Torque the mounting screws to 15 in/lbs to ensure they are securely fastened.

3. Post Installation:

- After installation, doublecheck that all screws are tightened and that the sight is securely mounted.
- Test the functionality of the red dot sight before use.

Disposal Instructions

- Dispose of any packaging materials in accordance with local recycling regulations.
- If you need to dispose of the product, check with local waste management authorities for the proper disposal of aluminum and other materials.

Contact Information for Further Support

For any questions or concerns regarding the WALTHER PPQ TRIJICON RMR SIGHT MOUNT, please contact the manufacturer or your local dealer for assistance. Ensure you have the product details ready for a quicker response.

By following these safety instructions, you can ensure a safe and enjoyable experience with your WALTHER PPQ TRIJICON RMR SIGHT MOUNT. Always prioritize safety and responsible handling of firearms.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk