

RUGER SR9, SR40, SR45 VORTEX VIPER/VENOM SIGHT MOUNT - EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS RUGER SR9/SR40 BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Handgun Bases](#)

EGW's red dot sights are meant to be installed from the left to the right (with the muzzle facing forward). The dovetail has a progressive taper to allow for easier install. Simply remove the rear sight on your gun and replace it with EGW mount in order to mount your Vortex Viper/Venom, Burris FastFire, or Docter red-dot sight. You can take the mount off and replace your rear sight at any time. Mounting hardware included. Installation Instructions Remove the rear sight* Install the EGW Sight Mount in the dovetail Tighten set screw (if applicable) Place the red dot sight on the EGW Sight Mount (placing a small piece of paper between the red dot sight and the sight mount will make for easier removal and will keep Loctite off of the red dot sight.) Apply blue Loctite to the provided mounting screws Torque mounting screws to 15in/lbs 2 Button Head Cap Screws - Provided for Vortex Viper and Venom Sights 2 Flat Head Cap Screws - Provided for Burris FastFire and Docter Sights The screws that are included with this mount require a 5/64" allen wrench for installation. Modification of your firearm may nullify the manufacturer's warranty. This product should be installed and checked by a qualified gunsmith. No liability is expressed or implied for damage or injury which may result from improper installation or use of this product. Does not work with Ruger SR9E or Ruger SR22.



Attributes

- Name: [EGW SIGHT MOUNT FOR VORTEX VIPER/VENOM FITS RUGER SR9/SR40 BLACK](#)
- Manufacturer: [EGW](#)
- Product no.: 296000650
- Mfr. No.: 49290
- Colour: Black
- Material: Aluminum
- Model: SR40c,SR9,SR40,SR45,SR9C
- Number of Bases: 1-Piece
- Style: Tactical
- Weapon type: Ruger
- Delivery weight: 0.045kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 140mm
- UPC: 841370117598

Item details

Made in USA

Table of Contents

- Startpage
- RUGER SR9, SR40, SR45 VORTEX VIPER/VENOM SIGHT MOUNT USER SAFETY INSTRUCTIONS
- About Us

RUGER SR9, SR40, SR45 VORTEX VIPER/VENOM SIGHT MOUNT USER SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the RUGER SR9, SR40, SR45 Vortex Viper/Venom Sight Mount by EGW. This product is designed to enhance your shooting experience by allowing the installation of red dot sights. To ensure your safety and the proper functioning of this product, please read and follow these instructions carefully.

General Safety Guidelines

- Always ensure your firearm is unloaded before installing or removing the sight mount.
- Handle all firearms with care and follow standard safety practices.
- Ensure that the sight mount is compatible with your specific firearm model (Ruger SR9, SR40, SR45).
- Inspect the sight mount and all components for damage before installation.
- If you are unsure about any part of the installation process, consult a qualified gunsmith.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe products or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Modify your firearm only if you are knowledgeable about the process; improper modifications may void your warranty.
- Use the provided mounting hardware only; do not substitute with other screws or components.
- Ensure that the red dot sight is securely mounted to prevent it from becoming loose during use.
- Do not use the sight mount with Ruger SR9E or Ruger SR22 models.
- If you experience any issues with the sight mount or red dot sight, cease use immediately and seek assistance.

Instructions for Installation and Usage

1. Remove the Rear Sight

- Ensure the firearm is unloaded.
- Carefully remove the rear sight from your gun.

2. Install the EGW Sight Mount

- Place the EGW Sight Mount in the dovetail from left to right (with the muzzle facing forward).
- Tighten the set screw (if applicable).

3. Mount the Red Dot Sight

- Place the red dot sight on the EGW Sight Mount.
- To facilitate easier removal and prevent Loctite from contacting the sight, place a small piece of paper between the red dot sight and the sight mount.

4. Apply Loctite

- Apply blue Loctite to the provided mounting screws.

5. Torque the Screws

- Torque the mounting screws to 15 in/lbs.

- Use the following screws provided:
 - 2 Button Head Cap Screws for Vortex Viper and Venom Sights.
 - 2 Flat Head Cap Screws for Burris FastFire and Docter Sights.
- A 5/64" allen wrench is required for installation.

6. Final Check

- Doublecheck all screws for tightness and ensure the sight is securely mounted.

Disposal Instructions

- Dispose of any packaging materials according to local regulations.
- If you need to dispose of the sight mount, follow local electronic waste disposal guidelines to ensure environmental safety.

Contact Information for Further Support

For any inquiries or concerns regarding the installation or use of the RUGER SR9, SR40, SR45 Vortex Viper/Venom Sight Mount, please consult a qualified gunsmith or refer to the manufacturer's website for additional resources.

By following these guidelines, you can ensure the safe and effective use of your RUGER SR9, SR40, SR45 Vortex Viper/Venom Sight Mount. Thank you for your attention to safety, and enjoy your shooting experience!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk