

BROWNING A-BOLT LONG ACTION HD PICATINNY SCOPE MOUNT - EGW BROWNING A-BOLT LA 1-PIECE PICATINNY BASE 0 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

This mount comes standard with a bevel on both sides making it ambidextrous. EGW recommends measuring the hole spacing in your receiver to confirm it matches with the dimensions they have published. Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. EGW one-piece scope mounts are the obvious choice for hunters and tactical shooters alike. This mount is a Picatinny-style base and compatible with Picatinny or Weaver scope rings. EGW machines these in their shop using one of their machining centers. After machining, the mounts are tumbled, sand blasted, and Type III anodized for long lasting durability. Recommend: 0 MOA - if shooting 0-500 yards 20 MOA - if shooting 500-1000 yards When zeroing your rifle with a 20 MOA mount, EGW recommends zeroing at 200 yards. Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is sold separately). The entire mount and accessories (from the mounting screws and wrench down to the packaging) are made in the USA. This mount fits: Browning A-Bolt Long Action Please check your screw diameter. Regular Browning A-Bolts come with #6 screws. Browning AB3s come with #8 screws. This product is designed for the standard A-Bolt, not the AB3. EGW does offer a mount for the AB3. The part number for that is 43400 for a 0 MOA and 43402 for a 20 MOA. EGW does not currently offer a Browning A-Bolt that will work for the Mountain Titanium in .300WSM.



Attributes

- Name: [EGW BROWNING A-BOLT LA 1-PIECE PICATINNY BASE 0 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000766
- Mfr. No.: 81027
- Action Type: Long
- Colour: Black
- Elevation: 0 MOA
- Material: Aluminum
- Model: A-Bolt
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Browning
- Delivery weight: 0.091kg
- Shipping height: 25mm
- Shipping width: 102mm
- Shipping length: 229mm
- UPC: 841370114115

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for BROWNING ABOLT LONG ACTION HD PICATINNY SCOPE MOUNT
- About Us

Safety Instruction Guide for BROWNING ABOLT LONG ACTION HD PICATINNY SCOPE MOUNT

Introduction

Thank you for choosing the BROWNING ABOLT LONG ACTION HD PICATINNY SCOPE MOUNT. This guide provides essential safety instructions and usage information to ensure the safe and effective use of your scope mount. Please read this guide carefully before installation and use.

General Safety Guidelines

- Always handle firearms and firearm accessories with care.
- Ensure the mount is compatible with your specific firearm model.
- Check for any visible damage to the mount before use.
- Keep the mount out of reach of children and vulnerable individuals.
- Report any unsafe products or accidents to the appropriate authorities.
- Regularly check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Verify the screw diameter before installation:
 - Regular Browning ABolts use #6 screws.
 - Browning AB3s use #8 screws.
- This product is designed for the standard ABolt model only, not the AB3.
- Ensure the mount is securely fastened before use to prevent accidents.
- Use only recommended torque settings of 20 inch lbs for installation.
- Apply a drip of blue loctite to the screws to secure them in place (loctite sold separately).
- Always zero your rifle at the recommended distance based on the mount MOA:
 - 0 MOA for shooting 0500 yards.
 - 20 MOA for shooting 5001000 yards, with zeroing recommended at 200 yards.

Instructions for Installation and Usage

1. Preparation:

- Gather necessary tools, including a torque wrench and blue loctite.
- Ensure your workspace is clean and welllit.

2. Installation Steps:

- Check that the mounting holes on your receiver match the published dimensions.
- Align the mount with the mounting holes on the receiver.
- Insert the screws into the mounting holes, ensuring they fit correctly.
- Using a torque wrench, tighten the screws to 20 inch lbs.
- Apply a drip of blue loctite to each screw for added security.

3. PostInstallation Check:

- Verify that the mount is securely attached and does not wobble.
- Confirm that there are no obstructions preventing the scope from being mounted.

4. Usage:

- When mounting your scope, utilize the Picatinny cross slots for flexibility.
- Adjust the scope rings to your preferred positioning.
- Regularly check the mount and scope for any signs of loosening or damage during use.

Disposal Instructions

- Dispose of the mount and packaging materials in accordance with local regulations.
- Do not dispose of the mount in general waste if it is damaged or deemed unsafe.
- Recycle materials where possible.

Contact Information for Further Support

For further assistance or inquiries regarding safety concerns, please consult your retailer or manufacturer. Ensure you have your product details at hand for a more efficient response.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk