

BROWNING A-BOLT LONG ACTION HD PICATINNY SCOPE MOUNT - EGW BROWNING A-BOLT LA 1-PIECE PICATINNY BASE 20 MOA

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Rifle Bases](#)

This mount comes standard with a bevel on both sides making it ambidextrous. EGW recommends measuring the hole spacing in your receiver to confirm it matches with the dimensions they have published. Picatinny cross slots run the full length of the rail, which gives the shooter flexibility when mounting scope rings and other accessories. EGW one-piece scope mounts are the obvious choice for hunters and tactical shooters alike. This mount is a Picatinny-style base and compatible with Picatinny or Weaver scope rings. EGW machines these in their shop using one of their machining centers. After machining, the mounts are tumbled, sand blasted, and Type III anodized for long lasting durability. Recommend: 0 MOA - if shooting 0-500 yards 20 MOA - if shooting 500-1000 yards When zeroing your rifle with a 20 MOA mount, EGW recommends zeroing at 200 yards. Installation: EGW recommends 20 inch lbs of torque and a drip of blue loctite (loctite is sold separately). The entire mount and accessories (from the mounting screws and wrench down to the packaging) are made in the USA. This mount fits: Browning A-Bolt Long Action Please check your screw diameter. Regular Browning A-Bolts come with #6 screws. Browning AB3s come with #8 screws. This product is designed for the standard A-Bolt, not the AB3. EGW does offer a mount for the AB3. The part number for that is 43400 for a 0 MOA and 43402 for a 20 MOA. EGW does not currently offer a Browning A-Bolt that will work for the Mountain Titanium in .300WSM.



Attributes

- Name: [EGW BROWNING A-BOLT LA 1-PIECE PICATINNY BASE 20 MOA](#)
- Manufacturer: [EGW](#)
- Product no.: 296000767
- Mfr. No.: 81028
- Action Type: Long
- Colour: Black
- Elevation: 20 MOA
- Material: Aluminum
- Model: A-Bolt
- Number of Bases: 1-Piece
- Style: Picatinny Rail
- Weapon type: Browning
- Delivery weight: 0.091kg
- Shipping height: 25mm
- Shipping width: 127mm
- Shipping length: 229mm
- UPC: 841370114122

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for BROWNING ABOLT LONG ACTION HD PICATINNY SCOPE MOUNT
- About Us

Safety Instruction Guide for BROWNING ABOLT LONG ACTION HD PICATINNY SCOPE MOUNT

Introduction

Thank you for choosing the BROWNING ABOLT LONG ACTION HD PICATINNY SCOPE MOUNT. This product is designed to enhance your shooting experience by providing a secure and reliable mounting solution for your scope. To ensure your safety and the optimal performance of this product, please read and follow the safety guidelines and instructions provided in this guide.

General Safety Guidelines

- Ensure safe use of the product by following all instructions.
- Check for damage or wear before use; do not use if damaged.
- Always handle firearms and accessories with care and in accordance with local laws and regulations.
- Keep the product out of reach of children and unauthorized users.
- Report any unsafe conditions or product malfunctions to the relevant authorities.
- Stay informed about product recalls via the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Confirm that the mount is compatible with your Browning ABolt model.
- Verify the screw diameter before installation:
 - Regular Browning ABolts use #6 screws.
 - Browning AB3s use #8 screws.
- Use the mount only for its intended purpose; do not modify or alter it.
- When zeroing your rifle, follow the recommended settings:
 - Use 0 MOA for shooting distances of 0500 yards.
 - Use 20 MOA for shooting distances of 5001000 yards.
- Always ensure that the mount is securely attached before use.
- Use the recommended torque of 20 inch lbs and a drop of blue loctite during installation.

Instructions for Installation and Usage

1. **Preparation:** Gather all necessary tools, including a torque wrench and blue loctite (sold separately).
2. **Check Compatibility:** Ensure the mount fits your Browning ABolt Long Action.
3. **Screw Verification:** Confirm that you have the correct screw size:
 - #6 screws for standard Browning ABolts.
 - #8 screws for Browning AB3s.
4. **Installation:**
 - Align the mount with the receiver of your rifle.
 - Insert screws and tighten them gradually.
 - Apply torque to 20 inch lbs using a torque wrench.
 - Apply a drop of blue loctite to secure the screws.
5. **Final Check:** Ensure all screws are tight and the mount is stable before attaching your scope.
6. **Zeroing Your Rifle:** For a 20 MOA mount, zero your rifle at 200 yards for optimal accuracy.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- Consider recycling options for aluminum materials where applicable.

Contact Information for Further Support

For any inquiries or concerns regarding the safety and usage of the BROWNING ABOLT LONG ACTION HD PICATINNY SCOPE MOUNT, please reach out to the appropriate support channels.

Thank you for your attention to these safety guidelines. Your safety and satisfaction are our top priorities. Enjoy your shooting experience!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk