

1911 "MELT" BUSHING - EGW 1911 BLUE MELT BUSHING

[Handgun Parts](#) > [Barrel Parts](#) > [Barrel Bushings](#)

Gives Slide A Finished Look

Large flange eliminates the sharp edges and step of conventional bushings. 1911 fits Govt. Melt Bushings require a two piece guide rod set-up to disassemble your gun. The spring will need to be taken out of the back as well. The flange on the melt bushing is too large to allow a spring plug to pull out from the front.



Attributes

- Name: [EGW 1911 BLUE MELT BUSHING](#)
- Manufacturer: [EGW](#)
- Product no.: 296012100
- Mfr. No.: 14311B
- Finish: Blued
- Model: Government
- Style: Large Flange
- Weapon type: 1911
- Delivery weight: 0.018kg
- Shipping height: 28mm
- Shipping width: 81mm
- Shipping length: 114mm
- UPC: 841370103522

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for 1911 "MELT" BUSHING EGW 1911 BLUE MELT BUSHING
- About Us

Safety Instruction Guide for 1911 "MELT" BUSHING EGW 1911 BLUE MELT BUSHING

Introduction

Thank you for choosing the 1911 "MELT" Bushing by EGW. This guide provides essential safety instructions and information to ensure the safe use and installation of your product. Please read this manual carefully before use.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose as described in this manual.
- Always handle firearms with care and follow general firearm safety practices.
- Keep the bushing and all related components out of reach of children and unauthorized users.
- Regularly inspect the bushing for any signs of wear or damage before installation and use.
- If you are unsure about any aspect of installation or usage, consult a qualified gunsmith.

Specific Safety Precautions for Use

- The large flange design eliminates sharp edges; however, exercise caution during handling to avoid cuts or injuries.
- Ensure that you have a twopiece guide rod setup to facilitate disassembly.
- Remove the spring from the back of the gun before attempting to disassemble or install the bushing.
- The flange on the melt bushing is too large to allow a spring plug to be pulled out from the front; follow the correct disassembly procedures.
- If fitting is required, seek assistance from a qualified gunsmith to avoid improper installation that could lead to malfunction or injury.

Instructions for Installation and Usage

1. Preparation:

- Ensure you have the necessary tools for installation.
- Make sure the firearm is unloaded and pointed in a safe direction.

2. Disassembly:

- Remove the slide from the frame of the 1911.
- Remove the spring from the back of the gun.
- Use a twopiece guide rod setup to disassemble the gun.

3. Installation of the Melt Bushing:

- Align the melt bushing with the slide.
- Carefully insert the bushing into the slide, ensuring it is seated properly.
- Reassemble the firearm in the reverse order of disassembly.

4. PostInstallation Check:

- Inspect the installation to confirm that the bushing is secure.
- Test the firearm in a safe environment to ensure proper function.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding firearm components.
- Do not dispose of in regular household waste.
- Contact local authorities or a licensed firearms dealer for guidance on proper disposal methods.

Contact Information for Further Support

For any safety inquiries or concerns regarding the 1911 "MELT" Bushing, please reach out to the designated EU contact point provided with the product or refer to the manufacturer's website for further assistance.

Conclusion

Your safety is our priority. By following these guidelines and instructions, you can ensure the proper and safe use of the 1911 "MELT" Bushing. For any additional information or concerns, please consult a qualified professional. Thank you for choosing EGW.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk