

QUICK CHANGE JAW ASSEMBLY FOR CO-AX PRESS - FORSTER PRODUCTS, INC. QUICK CHANGE JAW ASSEMBLY LS-LARGE (0.531"-0.625")

[Reloading](#) > [Reloading Presses](#) > [Single Stage Presses](#)

Reloaders who use the Forster Co-Axial reloading press can take advantage of a quick-change system designed to hold shells, thanks to a set of spring-loaded jaws that contact the base of the cannelure. These self-acting jaws automatically close around the cartridge case as the press works, releasing the case once the press has done its work. Forster now offers a Quick-Change Jaw Assembly for its press, which makes swapping out these jaws for different case sizes a breeze. S-Large - holds .468" to .562" rim S-Small - holds .343" to .422" rim LS-Large - holds .531" to .625" rim LS-Small - holds .312" to .375" rim Each Forster Quick-Change Jaw Assembly allows for easy swapping of S or LS shell-holder jaws, allowing users to adjust the shell holders to accommodate cases ranging in size from .312-.625-inch shell rims. This saves an incredible amount of time when switching over to a new caliber, and it also avoids the frustration of losing springs or misplacing a spare set of shell-holder jaws. As an added bonus, with the Forster Quick-Change Jaw Assembly, there's no possibility of installing the jaws in the wrong direction, avoiding the frustration of assembling the wear plate in backwards or having a flipped jaw.



Attributes

- Name: [FORSTER PRODUCTS, INC. QUICK CHANGE JAW ASSEMBLY LS-LARGE \(0.531"-0.625"\)](#)
- Manufacturer: [FORSTER PRODUCTS, INC.](#)
- Product no.: 319000051
- Mfr. No.: 028271-203
- Delivery weight: 0.134kg
- Shipping height: 13mm
- Shipping width: 89mm
- Shipping length: 102mm
- UPC: 757253991394

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for QUICK CHANGE JAW ASSEMBLY FOR COAX PRESS
- About Us

Safety Instruction Guide for QUICK CHANGE JAW ASSEMBLY FOR COAX PRESS

Introduction

Thank you for choosing the Forster Quick Change Jaw Assembly for your CoAxial reloading press. This product is designed to enhance your reloading experience by allowing for quick and efficient changes between various shellholder jaws. To ensure your safety and the proper functioning of the product, please read and follow these safety instructions carefully.

General Safety Guidelines

- Ensure that all users read and understand these safety guidelines before using the product.
- Always use the Quick Change Jaw Assembly in accordance with the manufacturer's instructions.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the Quick Change Jaw Assembly for any signs of wear or damage before each use.
- If you encounter any issues or have concerns regarding the product's safety, cease use immediately and consult the manufacturer.

Specific Safety Precautions for Use

• Hazard Identification:

- Risk of injury from improper handling of the jaws.
- Potential for damage to the reloading press if jaws are not installed correctly.
- Risk of losing small parts such as springs during jaw changes.

• Instructions to Avoid Hazards:

- Always ensure the press is in a safe position and not under tension before changing jaws.
- Handle jaws carefully to avoid pinching fingers or hands.
- Follow the installation instructions precisely to prevent misalignment or damage.
- Use the correct size jaws for the specific cartridge cases being reloaded.

• Age Specific Warnings:

- This product is not intended for use by children. Ensure that all users are trained adults.
- Supervise inexperienced users closely while they familiarize themselves with the product.

Instructions for Installation and Usage

1. Installation:

- Ensure the CoAx press is securely mounted and powered off.
- Remove the existing jaw assembly by following the manufacturer's removal instructions.
- Select the appropriate jaw size (S or LS) for your cartridge case.
- Align the new jaw assembly with the press and securely fasten it in place according to the manufacturer's instructions.
- Doublecheck that the jaws are installed correctly and securely before operating the press.

2. Usage:

- Load the cartridge case into the press and ensure it is seated properly in the jaws.

- Operate the press according to the manufacturer's guidelines, ensuring that the jaws engage the base of the cannelure.
- Monitor the operation of the press to ensure that the jaws are functioning correctly and securely holding the cartridge case.
- After use, remove the cartridge case and inspect the jaws for any signs of wear or damage.

Disposal Instructions

- Dispose of the Quick Change Jaw Assembly responsibly at the end of its lifecycle.
- Do not dispose of the product in regular household waste. Instead, follow local regulations for the disposal of metal and plastic components.
- Consider recycling the materials where possible to minimize environmental impact.

Contact Information for Further Support

For any questions or concerns regarding the Quick Change Jaw Assembly, please refer to the manufacturer's contact details provided with the product packaging. It is important to reach out to the manufacturer for assistance with safety inquiries or product support.

Conclusion

By following these safety instructions, you can ensure a safe and effective reloading experience with your Forster Quick Change Jaw Assembly. Remember to always prioritize safety and consult the manufacturer's guidelines for best practices. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk