

QUICK CHANGE JAW ASSEMBLY FOR CO-AX PRESS - FORSTER PRODUCTS, INC. QUICK CHANGE JAW ASSEMBLY LS-SMALL (0.312"-0.375")

[Reloading](#) > [Reloading Presses](#) > [Single Stage Presses](#)

Reloaders who use the Forster Co-Axial reloading press can take advantage of a quick-change system designed to hold shells, thanks to a set of spring-loaded jaws that contact the base of the cannelure. These self-acting jaws automatically close around the cartridge case as the press works, releasing the case once the press has done its work. Forster now offers a Quick-Change Jaw Assembly for its press, which makes swapping out these jaws for different case sizes a breeze. S-Large - holds .468" to .562" rim S-Small - holds .343" to .422" rim LS-Large - holds .531" to .625" rim LS-Small - holds .312" to .375" rim Each Forster Quick-Change Jaw Assembly allows for easy swapping of S or LS shell-holder jaws, allowing users to adjust the shell holders to accommodate cases ranging in size from .312-.625-inch shell rims. This saves an incredible amount of time when switching over to a new caliber, and it also avoids the frustration of losing springs or misplacing a spare set of shell-holder jaws. As an added bonus, with the Forster Quick-Change Jaw Assembly, there's no possibility of installing the jaws in the wrong direction, avoiding the frustration of assembling the wear plate in backwards or having a flipped jaw.



Attributes

- Name: [FORSTER PRODUCTS, INC. QUICK CHANGE JAW ASSEMBLY LS-SMALL \(0.312"-0.375"\)](#)
- Manufacturer: [FORSTER PRODUCTS, INC.](#)
- Product no.: 319000052
- Mfr. No.: 028271-204
- Delivery weight: 0.122kg
- Shipping height: 13mm
- Shipping width: 102mm
- Shipping length: 165mm
- UPC: 757253991387

Item details

Made in USA

Table of Contents

- Startpage
- Safety Instruction Guide for QUICK CHANGE JAW ASSEMBLY FOR COAX PRESS
- About Us

Safety Instruction Guide for QUICK CHANGE JAW ASSEMBLY FOR COAX PRESS

Introduction

Thank you for choosing the Forster Quick Change Jaw Assembly for your CoAx Reloading Press. This product is designed to enhance your reloading experience by allowing for quick and easy changes between different case sizes. To ensure your safety and the effective use of this product, please read and follow these safety instructions carefully.

General Safety Guidelines

- Ensure safe use of the Quick Change Jaw Assembly and your reloading press by following all provided instructions.
- Be aware of potential risks associated with reloading equipment, including mechanical hazards and improper handling.
- Regularly check for updates regarding product recalls or safety alerts through the EU's Safety Gate system.
- Safeguards are in place for vulnerable groups, including children. Keep all reloading equipment out of reach of children.
- In case of productrelated incidents, report unsafe products or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Always wear appropriate safety gear, including safety glasses, while using the reloading press.
- Ensure that the reloading area is wellventilated and free from any flammable materials.
- Do not exceed the recommended size limits for the jaws. Use SSmall for .312" to .375" rim and SLarge for .468" to .562" rim, etc.
- Avoid using damaged or wornout jaws. Regularly inspect the assembly for any signs of wear or damage before use.
- Never attempt to modify or repair the Quick Change Jaw Assembly. Contact the manufacturer for any issues.

Instructions for Installation and Usage

1. Installation of Quick Change Jaw Assembly:

- Ensure the reloading press is turned off and unplugged before installation.
- Remove the existing jaw assembly by following the manufacturer's instructions.
- Align the new Quick Change Jaw Assembly with the mounting points on the press.
- Securely attach the assembly, ensuring it is properly seated and locked in place.

2. Using the Quick Change Jaw Assembly:

- Select the appropriate jaw size based on the cartridge case you are using.
- Insert the cartridge case into the assembly, allowing the springloaded jaws to grip the base of the cannelure.
- Operate the reloading press according to the manufacturer's instructions, ensuring the jaws automatically close around the case.
- After reloading is complete, the jaws will release the case automatically.

3. Switching Jaw Sizes:

- To switch jaw sizes, follow the installation steps to remove the current assembly.
- Replace with the desired jaw size and secure it as instructed.

Disposal Instructions

- Dispose of any packaging materials in accordance with local regulations.
- If the Quick Change Jaw Assembly becomes damaged beyond repair, refer to local waste disposal guidelines for safe disposal of mechanical parts.

Contact Information for Further Support

For any questions or concerns regarding the Quick Change Jaw Assembly, please reach out to the manufacturer or your point of purchase for further assistance.

By adhering to these safety instructions, you can ensure a safe and efficient reloading experience with the Forster Quick Change Jaw Assembly. Thank you for your attention to safety!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk