

308 AR SILENT CAPTURED SPRINGS GEN 2 - J P ENTERPRISES 308 AR SILENT CAPTURED SPRING GEN 2

[Rifle Parts](#) > [Receiver Parts](#) > [Recoil Parts](#) > [Recoil Springs](#)

The Gen 2 Drop-in captured-spring recoil system helps your AR function more smoothly and quieter without any permanent modifications. The carefully balanced, custom-ground buffer spring, combined with the JP LMOS buffer, greatly reduces friction and vibration - say goodbye to the annoying "spoon over a cheese grater" noise of conventional springs and buffers. Fits buffer tubes for both M4-style collapsible stocks and also, using the included spacer, the longer tubes for fixed rifle stocks. The Auxiliary Spring Rate Kits for the JP Silent Captured Spring allow custom tuning of the device to a given rifle. While the default spring offers the best performance for the widest range of configurations, a simple disassembly and reassembly of the JPSCS with a slightly different spring rate can yield truly optimized performance, particularly for rifles without an adjustable gas block. Benefits of the Gen 2 Silent Captured Spring include: New aluminum guide rod cuts overall weight Heavier masses translate to more buffering mass and chance of bolt bounce Full correspondence between SCS masses and H1, H2 and H3 buffers Additional mass added to both AR-10 and 9mm models for better, broader function Interchangeable buffers allow conversion between AR-15 and AR-10 models (and vice versa) Includes spacer to allow for installation in both carbine-length and rifle-length buffer tubes. The standard weight buffer weighs approximately 3.6 ounces. The buffer contains one Tungsten weight, and two steel weights.



Attributes

- Name: [JP ENTERPRISES 308 AR SILENT CAPTURED SPRING GEN 2](#)
- Manufacturer: [JP ENTERPRISES](#)
- Product no.: 452000213
- Mfr. No.: JPSCS2-10
- Weapon type: AR .308
- Delivery weight: 0.136kg
- Shipping height: 25mm
- Shipping width: 76mm
- Shipping length: 229mm
- UPC: 812872023991

Item details

Made in USA

US export classification: 0A501.x

Table of Contents

- Startpage
- Safety Instruction Guide for 308 AR Silent Captured Springs Gen 2
- About Us

Safety Instruction Guide for 308 AR Silent Captured Springs Gen 2

Introduction

Thank you for choosing the 308 AR Silent Captured Springs Gen 2 by J P Enterprises. This guide provides essential safety instructions and usage guidelines to ensure the safe operation of your product. Please read this manual carefully before using the product to maximize safety and performance.

General Safety Guidelines

- **Product Safety:** This product is designed for safe use in nonfood applications. Ensure that you follow all instructions to avoid risks.
- **Enhanced Recalls:** Stay informed about any recall notices. If you receive a recall notice, please follow the instructions provided for a remedy.
- **Online Shopping:** When purchasing online, ensure that the seller complies with safety regulations similar to those in physical stores.
- **Special Consumer Focus:** This product is not intended for use by children. Keep it out of reach of minors.
- **EU Contact Point:** For any safety inquiries, please contact an authorized representative within the EU.
- **Rapid Alerts:** Monitor the EU's Safety Gate platform for updates regarding unsafe products.

Specific Safety Precautions for Use

- **Installation:** Ensure that the buffer spring is installed correctly according to the provided instructions. Incorrect installation can lead to malfunction.
- **Inspection:** Regularly inspect the product for wear and tear. Replace any damaged components immediately.
- **Handling:** Always handle the product with care to avoid injury. Use appropriate protective gear when necessary.
- **Compatibility:** Ensure that the product is compatible with your firearm model. Check specifications before use.
- **Storage:** Store the product in a cool, dry place away from direct sunlight and moisture to prevent damage.

Instructions for Installation and Usage

1. Preparation:

- Ensure that your firearm is unloaded and safe to work on.
- Gather all necessary tools and components for installation.

2. Installation Steps:

- Remove the existing buffer and spring from your firearm.
- Insert the JP Silent Captured Spring into the buffer tube, ensuring it is seated properly.
- If using a fixed rifle stock, utilize the included spacer for proper fitment.
- Reinstall the buffer retaining pin and ensure everything is secure.

3. Usage:

- After installation, test the firearm in a safe environment to ensure proper function.
- Monitor the performance during use. If you notice any irregularities, cease use immediately and

inspect the installation.

4. Adjustment:

- If necessary, disassemble the JP Silent Captured Spring and replace it with an Auxiliary Spring Rate Kit for custom tuning.
- Follow the same installation steps for any adjustments or replacements.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic waste and firearm accessories.
- Do not throw the product in regular household waste.
- Contact your local waste management facility for proper disposal methods.

Contact Information for Further Support

For further assistance or inquiries regarding the 308 AR Silent Captured Springs Gen 2, please refer to the manufacturer's contact information provided with your product packaging.

By following these safety instructions, you can ensure a safe and enjoyable experience with your 308 AR Silent Captured Springs Gen 2. Thank you for your attention to safety!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk