

LEWIS LEAD REMOVER - BROWNELLS LEWIS LEAD REMOVER ADAPTER KIT, 40/41 CALIBER

[Gun Cleaning & Chemicals](#) > [Patches & Mops](#) > [Lead Remover](#)

Traditional - And Still The Best Mechanical Deleader

Lead fouling can build up in the forcing cone, barrel, and chamber of a pistol, ruining accuracy completely. The Lewis Lead Remover is the single best way to remove all leading easily, plus will not damage the gun in any way. Used and endorsed by the nation's top shooters. Use with J-B Bore Cleaner for the cleanest, lead-free barrel ever!



Attributes

- Name: [BROWNELLS LEWIS LEAD REMOVER ADAPTER KIT, 40/41 CALIBER](#)
- Manufacturer: [BROWNELLS](#)
- Product no.: 516150041
- Mfr. No.:
- Caliber: 41 Caliber (.410-.412)
- Delivery weight: 0.018kg
- UPC: 050806022867

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [LEWIS LEAD REMOVER SAFETY INSTRUCTIONS](#)
- [About Us](#)

LEWIS LEAD REMOVER SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the Lewis Lead Remover. This product is designed to effectively remove lead fouling from your firearm, ensuring optimal performance and accuracy. Please read this safety instruction guide carefully to ensure safe and proper use.

General Safety Guidelines

- Always follow the manufacturer's instructions for use.
- Keep the product out of reach of children.
- Use the product only for its intended purpose as described in this guide.
- Inspect the product for any damage before use. Do not use if damaged.
- Store the product in a cool, dry place away from direct sunlight.
- If you experience any adverse reactions while using this product, discontinue use immediately and seek medical attention if necessary.

Specific Safety Precautions for Use

- Use protective eyewear when operating the Lewis Lead Remover to prevent any lead particles from entering your eyes.
- Wear gloves to minimize skin contact with lead and cleaning materials.
- Ensure that the area where you use the product is wellventilated to avoid inhaling any fumes or dust.
- Do not use the product on firearms that are loaded. Always ensure your firearm is unloaded before cleaning.
- Keep the product away from open flames or high heat sources.

Instructions for Installation and Usage

Components Included in the Kit

The Lead Remover Kit contains the following components:

- Handle
- Cone tip
- Rubber tip
- Specially woven brass patches
- Complete instructions

Installation Instructions

1. **Assemble the Handle:** Attach the cone tip or rubber tip to the handle based on your cleaning needs.
2. **Prepare the Firearm:** Ensure that your firearm is completely unloaded. Remove any ammunition from the vicinity.
3. **Insert the Patch:** Place a specially woven brass patch onto the cone tip or rubber tip.
4. **Begin Cleaning:** Insert the tip into the barrel and gently twist while pulling it through. Repeat as necessary until the lead fouling is removed.
5. **Use with JB Bore Cleaner:** For optimal results, follow up with JB Bore Cleaner to ensure a leadfree barrel.

PostUsage Instructions

- After use, clean the components with a suitable cleaning solution and store them safely.
- Dispose of any used patches and materials in accordance with local regulations regarding lead disposal.

Disposal Instructions

- Dispose of the product and any used components in accordance with local regulations.
- Do not dispose of lead materials in regular household waste. Contact your local waste management facility for proper disposal methods.

Contact Information for Further Support

For safety inquiries or further assistance, please refer to the manufacturer's contact details provided on the packaging or product documentation.

By following these safety instructions, you can ensure a safe and effective experience with the Lewis Lead Remover. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk