

INTERLOCK 6.5MM (0.264") SST BULLETS - SST 6.5MM (0.264") 129GR POLYMER TIP BOAT TAIL 100/BOX

[Reloading](#) > [Bullets](#) > [Rifle Bullets](#)

Hornady SST Bullets feature a streamlined profile for ultra-flat trajectories. Polymer tip allows for rapid expansion and maximum energy transfer. Match-grade jacket delivers surgical accuracy. Heavy construction with InterLock feature delivers deep penetration every time.



Attributes

- Name: [SST 6.5MM \(0.264"\) 129GR POLYMER TIP BOAT TAIL 100/BOX](#)
- Manufacturer: [HORNADY](#)
- Product no.: 749004021
- Mfr. No.: 26202
- Ballistic Coefficient (G1): 0.485
- Brand Style: InterLock
- Bullet Style: Super Shock Tip (SST)
- Caliber: 6.5mm,264 Caliber
- Diameter (Breech): 0.264
- Diameter (in): 0.264
- Grain: 129
- Sectional Density: 0.264
- Quantity: 100
- Delivery weight: 0.839kg
- Shipping height: 56mm
- Shipping width: 69mm
- Shipping length: 107mm
- UPC: 090255262025

Item details

Made in USA

US export classification: 0A505.x

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for Hornady INTERLOCK 6.5MM \(0.264"\) SST Bullets](#)
- [About Us](#)

Safety Instruction Guide for Hornady INTERLOCK 6.5MM (0.264") SST Bullets

Introduction

Thank you for choosing Hornady INTERLOCK 6.5MM (0.264") SST Bullets. This guide provides essential safety information to ensure the safe and effective use of this product. Please read and follow all instructions carefully to minimize risks and maximize safety.

General Safety Guidelines

- Always handle bullets with care and respect.
- Store bullets in a cool, dry place away from direct sunlight and moisture.
- Keep bullets out of reach of children and unauthorized users.
- Use only in accordance with the manufacturer's instructions and local laws.
- Regularly check for any product recalls or safety updates.

Specific Safety Precautions for Use

- Always wear appropriate personal protective equipment (PPE) such as safety glasses and hearing protection when loading or firing.
- Ensure that your firearm is compatible with 6.5MM (0.264") bullets before use.
- Inspect bullets for any signs of damage or defects before loading.
- Do not exceed the recommended load specifications for your firearm.
- Be aware of your surroundings and ensure a safe shooting environment.
- Never point a firearm at anything you do not intend to shoot.

Instructions for Installation and Usage

• Loading the Bullets:

1. Ensure your firearm is pointed in a safe direction.
2. Open the ammunition compartment according to your firearm's instructions.
3. Carefully insert the Hornady SST bullets into the magazine or chamber as specified by your firearm's manual.
4. Close the compartment securely.

• Firing the Bullets:

1. Ensure that you are in a safe shooting area.
2. Load the firearm following the manufacturer's instructions.
3. Stand in a stable shooting position.
4. Aim at your target and ensure a clear line of sight.
5. Pull the trigger gently to fire.

• PostFiring:

1. After firing, always treat the firearm as if it is loaded.
2. Unload the firearm according to the manufacturer's instructions.
3. Store the firearm and bullets securely.

Disposal Instructions

- Dispose of any unused or expired bullets in accordance with local regulations.
- Do not throw bullets in regular trash.
- Contact local waste management authorities for guidance on proper disposal methods.

Contact Information for Further Support

For any safety inquiries or concerns regarding the Hornady INTERLOCK 6.5MM (0.264") SST Bullets, please reach out to the manufacturer or your local distributor. It is essential to have a reliable contact for any safety issues or product recalls.

Conclusion

By following these safety instructions, you can ensure a safe and enjoyable experience with Hornady INTERLOCK 6.5MM (0.264") SST Bullets. Always prioritize safety and be informed about your responsibilities as a user. Thank you for choosing Hornady.

About Us

Brownells Česká republika

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.cz