

ULTRALIGHT RINGS - 30MM LOW .885" 4 SCREW ULTRALIGHT RINGS

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Designed to fit Mil-Std. 1913 scope bases, Nightforce rings are precisely manufactured to match the machined recess of a Nightforce Mil-Std. 1913 base, providing perfect alignment and accuracy. Nightforce rings are designed and produced in-house to exacting specifications entirely out of steel or from 7075-T6 aluminum with beta series titanium crossbolts and jaws. All Nightforce rings are 100% micro-radiused and honed in pairs for perfect fit of 30mm scope tubes to prevent the possibility of the rings damaging your scope.



Attributes

- Name: [30MM LOW .885" 4 SCREW ULTRALIGHT RINGS](#)
- Manufacturer: [NIGHTFORCE](#)
- Product no.: 749012011
- Mfr. No.: A118
- Finish: Matte
- Height: Low
- Material: -
- Scope Tube Diameter: 30mm
- Size: -
- Style: Picatinny Rings
- Delivery weight: 0.091kg
- Shipping height: 25mm
- Shipping width: 114mm
- Shipping length: 76mm
- UPC: 847362003108

Item details

Made in USA

Table of Contents

- Startpage
- [ULTRALIGHT RINGS 30MM LOW .885" 4 SCREW ULTRALIGHT RINGS Safety Instruction Guide](#)
- About Us

ULTRALIGHT RINGS 30MM LOW .885" 4 SCREW

ULTRALIGHT RINGS Safety Instruction Guide

Introduction

Thank you for choosing the ULTRALIGHT RINGS 30MM LOW .885" 4 SCREW ULTRALIGHT RINGS by NIGHTFORCE. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your scope rings. Please read this document carefully before installation and use.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Inspect the product for any signs of damage or wear before each use.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe product conditions or accidents to the relevant authorities.
- Stay informed about product recalls by checking the EU's Safety Gate platform regularly.

Specific Safety Precautions for Use

- Always ensure that the scope rings are compatible with your scope and rifle before installation.
- Do not exceed the recommended torque specifications during installation to prevent damage.
- Avoid using the scope rings if they show any signs of deformation or damage.
- Be cautious when handling sharp tools during installation to avoid injury.
- Ensure that the scope is securely mounted to prevent it from detaching during use.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools, including a torque wrench and appropriate screws.
- Ensure that your workspace is clean and free of distractions.

2. Installation Steps

- Start by placing the scope rings on the MilStd. 1913 scope base.
- Align the rings with the machined recess of the base for perfect fit and alignment.
- Insert the screws into the rings and handtighten them to hold the rings in place.
- Using a torque wrench, tighten the screws to the manufacturer's recommended torque specifications.
- Check for proper alignment of the scope within the rings.

3. Usage

- Once installed, regularly check the tightness of the screws before each use.
- Monitor the scope for any signs of movement or misalignment during use.
- Store your firearm and scope in a safe place when not in use.

Disposal Instructions

- Dispose of any packaging materials in accordance with local recycling regulations.
- If the product is damaged beyond repair, dispose of it responsibly to minimize environmental impact.

Contact Information for Further Support

For any safety inquiries or further support regarding the ULTRALIGHT RINGS 30MM LOW .885" 4 SCREW ULTRALIGHT RINGS, please refer to the appropriate contact channels as indicated in your product documentation.

Thank you for your attention to these safety guidelines. Enjoy using your ULTRALIGHT RINGS with confidence!

About Us

Brownells Česká republika

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.cz