

CONTOUR #5 BARREL - SHILEN 20 CALIBER 1-12 TWIST #5 STAINLESS BARREL

[Gunsmith Tools](#) > [Barrel Tools](#) > [Barrel Blanks](#)

Contour #5 in Chrome Moly or Stainless Steel

All the loving care of the best stockmaker and the meticulous attention to detail of the master machinist will not make a gun shoot any straighter than the accuracy capability of the barrel used. And, it is the insides of a barrel, that very small and vital area of lands and grooves over which the gunsmith has no control, that can determine whether the finished work of art is for shooting - or "just for looks". Craftsmanship . . . not price . . . determines the quality of a barrel. But, by the same token, the customer willing to spend the money for a custom gun is shortsighted indeed, if he starts economizing and orders "just any old barrel so long as it's cheap". Furthermore, he is jeopardizing your reputation as a gun builder by making such a request. We, as your supplier, are laying our reputation (and yours, too!) on the line by offering you barrel blanks. They have got to be good or we are in trouble! Big trouble!! We must never sell you anything but that which will enlarge your stature with your trade. And, we feel that the Brownell Barrel, made for us by Ed Shilen, will do just that! Shilen barrels, either chrome moly or Stainless, are rifled with six lands and grooves by the "Cold Forming" process using carbide dies made in Shilen's own plant under the most rigid controls. This rifling method achieves extremely close inside uniformity from breech to muzzle. Finished barrels are air-gauge inspected (air-gauged sensitivity is .00005" - five-one-hundred-thousandths!) and 6X borescope inspected. All barrels, .22 through .30 caliber have groove tolerances within .0005" and uniformity within .0003". No straightening is done, and all barrels are completely stress-relieved. All stainless steel barrels are hand lapped at the factory. Only those barrels passing all spec tests are offered to the trade. Any barrel even slightly "suspect" is started through the production process again and bored to a large caliber. In no other way can quality and reputation be maintained. Slightly more expensive to produce - but vastly greater in quality and ultimate performance.



Attributes

- Name: [SHILEN 20 CALIBER 1-12 TWIST #5 STAINLESS BARREL](#)
- Manufacturer: [SHILEN](#)
- Product no.: 787000019
- Mfr. No.: 20125SS
- Caliber: 20 Caliber (.204)
- Contour: #5
- Material: Stainless Steel
- Style: Match-Grade
- Twist: 1-12
- Delivery weight: 1.973kg
- Shipping height: 28mm
- Shipping width: 30mm
- Shipping length: 711mm

Item details

Made in USA

US export classification: 0A501.c

Table of Contents

- Startpage
- Safety Instruction Guide for CONTOUR #5 BARREL SHILEN 20 CALIBER
- About Us

Safety Instruction Guide for CONTOUR #5 BARREL SHILEN 20 CALIBER

Introduction

Thank you for choosing the CONTOUR #5 BARREL SHILEN 20 CALIBER. This guide provides essential safety instructions to ensure the safe use of this product, in compliance with the EU General Product Safety Regulation (GPSR). Please read this guide carefully before using the barrel to ensure safe handling and optimal performance.

General Safety Guidelines

- Always handle the barrel with care and follow all safety protocols when using firearms.
- Ensure that the barrel is compatible with your firearm model before installation.
- Store the barrel in a secure location, away from children and unauthorized users.
- Regularly inspect the barrel for any signs of damage or wear before use.
- Report any unsafe conditions or incidents to the relevant authorities immediately.
- Check for recall updates on the EU's Safety Gate platform to stay informed about any safety issues.

Specific Safety Precautions for Use

- Do not attempt to modify or alter the barrel in any way.
- Ensure that you are using appropriate ammunition that matches the specifications of the barrel (20 Caliber).
- Always wear appropriate safety gear, including eye protection, when handling firearms.
- Be aware of your surroundings and ensure that you are in a safe environment when shooting.
- If you notice any irregularities in performance, stop using the barrel immediately and consult a professional gunsmith.

Instructions for Installation and Usage

1. Installation:

- Ensure that your firearm is unloaded and pointed in a safe direction before beginning installation.
- Follow the manufacturer's instructions for your specific firearm model to remove the existing barrel.
- Carefully align the CONTOUR #5 BARREL with the firearm's receiver and secure it according to the manufacturer's guidelines.
- Check that the barrel is properly fitted and all screws or bolts are tightened securely.

2. Usage:

- Before shooting, perform a thorough inspection of the barrel and ensure it is clean and free of obstructions.
- Load the firearm with appropriate ammunition and ensure that the safety mechanism is engaged until ready to fire.
- Always maintain a safe shooting stance and keep the firearm pointed in a safe direction.
- After use, clean the barrel according to the manufacturer's recommendations to maintain its performance and longevity.

Disposal Instructions

- Dispose of the barrel in accordance with local regulations regarding metal recycling and firearm components.
- Do not dispose of the barrel in regular household waste.
- If you are unsure about disposal methods, consult local authorities for guidance.

Contact Information for Further Support

For any inquiries regarding safety concerns or product performance, please refer to the manufacturer's contact details provided with your purchase. It is important to reach out for professional assistance when needed.

Thank you for prioritizing safety while using the CONTOUR #5 BARREL SHILEN 20 CALIBER. Your adherence to these guidelines ensures a safer experience for yourself and others.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk