

# CONTOUR #2 - SHILEN 6MM 1-10 TWIST #2 CHROME MOLY BARREL

[Rifle Parts](#) > [Barrel Parts](#) > [Rifle Barrel Blanks](#)

## Contour #2 in Chrome Moly or Stainless Steel

All the loving care of the best stockmaker and the meticulous attention to detail of the master machinist will not make a gun shoot any straighter than the accuracy capability of the barrel used. And, it is the insides of a barrel, that very small and vital area of lands and grooves over which the gunsmith has no control, that can determine whether the finished work of art is for shooting - or "just for looks". Craftsmanship . . . not price . . . determines the quality of a barrel. But, by the same token, the customer willing to spend the money for a custom gun is shortsighted indeed, if he starts economizing and orders "just any old barrel so long as it's cheap". Furthermore, he is jeopardizing your reputation as a gun builder by making such a request. We, as your supplier, are laying our reputation (and yours, too!) on the line by offering you barrel blanks. They have got to be good or we are in trouble! Big trouble!! We must never sell you anything but that which will enlarge your stature with your trade. And, we feel that the Brownell Barrel, made for us by Ed Shilen, will do just that! Shilen barrels, either chrome moly or Stainless, are rifled with six lands and grooves by the "Cold Forming" process using carbide dies made in Shilen's own plant under the most rigid controls. This rifling method achieves extremely close inside uniformity from breech to muzzle. Finished barrels are air-gauge inspected (air-gauged sensitivity is .00005" - five-one-hundred-thousandths!) and 6X borescope inspected. All barrels, .22 through .30 caliber have groove tolerances within .0005" and uniformity within .0003". No straightening is done, and all barrels are completely stress-relieved. All stainless steel barrels are hand lapped at the factory. Only those barrels passing all spec tests are offered to the trade. Any barrel even slightly "suspect" is started through the production process again and bored to a large caliber. In no other way can quality and reputation be maintained. Slightly more expensive to produce - but vastly greater in quality and ultimate performance.



## Attributes

- Name: [SHILEN 6MM 1-10 TWIST #2 CHROME MOLY BARREL](#)
- Manufacturer: [SHILEN](#)
- Product no.: 787243102
- Mfr. No.: 6MM102CM
- Caliber: 243/6 mm (.243)
- Contour: #2
- Material: Chrome Moly Steel
- Style: Match-Grade
- Twist: 1-10
- Delivery weight: 1.406kg
- Shipping height: 28mm
- Shipping width: 28mm
- Shipping length: 660mm

## Item details

Made in USA

US export classification: 0A501.c

# Table of Contents

- [Startpage](#)
- [CONTOUR #2 SHILEN 6MM 110 TWIST #2 CHROME MOLY BARREL Safety Instruction Guide](#)
- [About Us](#)

# CONTOUR #2 SHILEN 6MM 110 TWIST #2 CHROME MOLY BARREL Safety Instruction Guide

## Introduction

Thank you for choosing the CONTOUR #2 SHILEN 6MM 110 TWIST #2 CHROME MOLY BARREL. This guide provides essential safety instructions to ensure the safe use and handling of your barrel. Please read this manual carefully to understand the proper procedures and precautions.

## General Safety Guidelines

- Ensure that all users of this product are familiar with firearm safety practices.
- Always treat the firearm as if it is loaded.
- Use the barrel only for its intended purpose as specified by the manufacturer.
- Regularly inspect the barrel for any signs of damage or wear before use.
- Store the barrel in a secure location, away from children and unauthorized users.
- Follow all local laws and regulations regarding firearm ownership and use.
- Report any unsafe products or incidents to the appropriate authorities.

## Specific Safety Precautions for Use

- Always wear appropriate eye protection when using firearms equipped with this barrel.
- Ensure that the barrel is properly installed according to the instructions provided.
- Do not exceed the recommended caliber specifications for this barrel.
- Avoid using ammunition that is not compatible with the barrel specifications.
- Do not attempt to modify the barrel in any way.
- In case of a misfire, keep the firearm pointed in a safe direction and wait at least 30 seconds before attempting to clear the chamber.
- If you notice any unusual sounds or behaviors during use, cease operation immediately and inspect the barrel.

## Instructions for Installation and Usage

### 1. Installation:

- Ensure that the firearm is unloaded before beginning installation.
- Use appropriate tools to securely attach the barrel to the firearm's action.
- Follow the manufacturer's specifications for torque settings during installation.
- Inspect the alignment of the barrel to ensure it is properly seated.

### 2. Usage:

- Before using the firearm, perform a thorough inspection of the barrel and firearm.
- Load the firearm with compatible ammunition only.
- Maintain a proper shooting stance and grip while using the firearm.
- Always be aware of your surroundings and ensure a clear line of fire.

## Disposal Instructions

- Dispose of the barrel in accordance with local regulations regarding metal and firearm components.
- Do not dispose of the barrel in regular household waste.
- Consider recycling the barrel through a licensed facility that handles firearm components.

## **Contact Information for Further Support**

For any questions or concerns regarding the safety and use of the CONTOUR #2 SHILEN 6MM 110 TWIST #2 CHROME MOLY BARREL, please refer to the manufacturer's contact information provided in the product packaging or visit the manufacturer's website.

Please keep this safety instruction guide for future reference and ensure that all users of the product are aware of these safety guidelines. Thank you for prioritizing safety while using your CONTOUR #2 SHILEN barrel.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)