

CONTOUR #2 - SHILEN 338 CALIBER 1-10 TWIST #2 CHROME MOLY BARREL

[Rifle Parts](#) > [Barrel Parts](#) > [Rifle Barrel Blanks](#)

Contour #2 in Chrome Moly or Stainless Steel

All the loving care of the best stockmaker and the meticulous attention to detail of the master machinist will not make a gun shoot any straighter than the accuracy capability of the barrel used. And, it is the insides of a barrel, that very small and vital area of lands and grooves over which the gunsmith has no control, that can determine whether the finished work of art is for shooting - or "just for looks". Craftsmanship . . . not price . . . determines the quality of a barrel. But, by the same token, the customer willing to spend the money for a custom gun is shortsighted indeed, if he starts economizing and orders "just any old barrel so long as it's cheap". Furthermore, he is jeopardizing your reputation as a gun builder by making such a request. We, as your supplier, are laying our reputation (and yours, too!) on the line by offering you barrel blanks. They have got to be good or we are in trouble! Big trouble!! We must never sell you anything but that which will enlarge your stature with your trade. And, we feel that the Brownell Barrel, made for us by Ed Shilen, will do just that! Shilen barrels, either chrome moly or Stainless, are rifled with six lands and grooves by the "Cold Forming" process using carbide dies made in Shilen's own plant under the most rigid controls. This rifling method achieves extremely close inside uniformity from breech to muzzle. Finished barrels are air-gauge inspected (air-gauged sensitivity is .00005" - five-one-hundred-thousandths!) and 6X borescope in- spected. All barrels, .22 through .30 caliber have groove tolerances within .0005" and uniformity within .0003". No straightening is done, and all barrels are completely stress-relieved. All stainless steel barrels are hand lapped at the factory. Only those barrels passing all spec tests are offered to the trade. Any barrel even slightly "suspect" is started through the production process again and bored to a large caliber. In no other way can quality and reputation be maintained. Slightly more expensive to produce - but vastly greater in quality and ultimate performance.



Attributes

- Name: [SHILEN 338 CALIBER 1-10 TWIST #2 CHROME MOLY BARREL](#)
- Manufacturer: [SHILEN](#)
- Product no.: 787338102
- Mfr. No.: 338102CM
- Caliber: 338 Caliber (.338)
- Contour: #2
- Material: Chrome Moly Steel
- Style: Match-Grade
- Twist: 1-10
- Delivery weight: 1.27kg
- Shipping height: 28mm
- Shipping width: 28mm
- Shipping length: 660mm

Item details

Made in USA

US export classification: 0A501.c

Table of Contents

- Startpage
- Safety Instruction Guide for CONTOUR #2 SHILEN 338 CALIBER 110 TWIST #2 CHROME MOLY BARREL
- About Us

Safety Instruction Guide for CONTOUR #2 SHILEN 338 CALIBER 110 TWIST #2 CHROME MOLY BARREL

Introduction

Thank you for choosing the CONTOUR #2 SHILEN 338 CALIBER 110 TWIST #2 CHROME MOLY BARREL. This guide provides essential safety instructions and guidelines to ensure the safe use and handling of your barrel. Please read this document carefully before installation and use.

General Safety Guidelines

- Always handle firearms and firearm components with care and respect.
- Ensure that the barrel is compatible with your firearm before installation.
- Keep the barrel and all firearm components out of reach of children and unauthorized users.
- Regularly inspect the barrel for any signs of wear or damage.
- Follow all local laws and regulations regarding firearms and their components.

Specific Safety Precautions for Use

- Do not use the barrel if you notice any defects or irregularities.
- Ensure that the barrel is properly installed and secured before use.
- Always wear appropriate eye and ear protection when using firearms.
- Do not exceed the recommended ammunition specifications for your barrel.
- Be aware of your surroundings and ensure a safe shooting environment.

Instructions for Installation and Usage

1. Preparation:

- Ensure that the firearm is unloaded and pointed in a safe direction.
- Gather all necessary tools for installation.

2. Installation:

- Remove the existing barrel from your firearm according to the manufacturer's instructions.
- Carefully align the CONTOUR #2 SHILEN barrel with the receiver.
- Securely fasten the barrel using the appropriate tools, ensuring that it is properly torqued according to the specifications provided by the firearm manufacturer.
- Inspect the installation to ensure there are no gaps or misalignments.

3. Usage:

- Load the firearm with the appropriate ammunition for the 338 caliber.
- Conduct a function check to ensure proper operation before live firing.
- Follow all safety protocols and guidelines for shooting.

Disposal Instructions

- When disposing of the barrel, ensure that it is done in accordance with local regulations.
- Do not dispose of the barrel in regular waste.
- Consider recycling options for metal components where available.

Contact Information for Further Support

For any safety inquiries or further support, please refer to the manufacturer's contact details provided with your product packaging or visit the official website.

Conclusion

By following these safety instructions and guidelines, you can ensure a safe and enjoyable experience with your CONTOUR #2 SHILEN 338 CALIBER 110 TWIST #2 CHROME MOLY BARREL. Always prioritize safety and compliance with local regulations. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk