

TEMPILAQ® - TEMPILAQ 2 OZ. 450° F.

[Gunsmith Tools](#) > [Metal Prep & Coloring](#) > [Heat-Treating Accessories](#)

Positive Heat Indicator When Heat Treating

Laboratory control, minimum cost. For furnace or open flame hardening and tempering of steel parts. Apply thin smear to surface to be treated. When desired temperature is reached, Tempilaq melts sharply. Disregard color changes, when Tempilaq melts, quench!



Attributes

- Name: [TEMPILAQ 2 OZ. 450° F.](#)
- Manufacturer: [TEMPILAQ](#)
- Product no.: 877450002
- Mfr. No.: 024413
- Delivery weight: 0.159kg
- Shipping height: 762mm
- Shipping width: 41mm
- Shipping length: 43mm
- UPC: 048615244136

Item details

Made in USA

Table of Contents

- Startpage
- TEMPILAQ® 2 OZ. 450° F Safety Instruction Guide
- About Us

TEMPILAQ® 2 OZ. 450° F Safety Instruction Guide

Introduction

Thank you for choosing TEMPILAQ® for your heat treating needs. This guide provides important safety instructions to ensure safe usage of the product. Please read and follow these guidelines carefully to avoid potential hazards.

General Safety Guidelines

- Always wear appropriate personal protective equipment (PPE), including gloves and safety goggles, when handling TEMPILAQ®.
- Ensure that the area where TEMPILAQ® is used is well ventilated to prevent inhalation of fumes.
- Keep TEMPILAQ® out of reach of children and pets to prevent accidental exposure.
- Store TEMPILAQ® in a cool, dry place away from direct sunlight and heat sources.
- Follow local regulations for the safe disposal of chemical products.

Specific Safety Precautions for Use

• Hazard Identification:

- TEMPILAQ® is a flammable liquid. Avoid open flames and sources of ignition.
- The product may cause skin and eye irritation. Use with care and avoid direct contact.

• Avoiding Hazards:

- Do not apply TEMPILAQ® near open flames or hot surfaces.
- In case of skin contact, wash the affected area with soap and water immediately.
- If TEMPILAQ® gets into the eyes, rinse thoroughly with water for at least 15 minutes and seek medical attention.
- Do not inhale vapors; use in a well ventilated area or with appropriate respiratory protection.

Instructions for Installation and Usage

• Application:

- Shake the bottle before use to ensure an even consistency.
- Apply a thin smear of TEMPILAQ® to the surface of the steel parts to be treated.
- Monitor the temperature closely. TEMPILAQ® will melt sharply when the desired temperature is reached.
- Disregard any color changes; once TEMPILAQ® melts, quench the parts immediately to achieve the desired hardness.

• Storage:

- After use, securely close the bottle to prevent evaporation and contamination.
- Keep the bottle upright to avoid spills.

Disposal Instructions

- Dispose of any unused TEMPILAQ® according to local hazardous waste disposal regulations.
- Do not pour TEMPILAQ® down the drain or into water bodies.
- Ensure that the container is completely empty before recycling or disposing of it.

Contact Information for Further Support

For any safety inquiries or concerns regarding TEMPILAQ®, please consult your local distributor or the manufacturer's website for further assistance.

By following these safety instructions, you can ensure a safe and effective experience with TEMPILAQ®. Thank you for your attention to these important guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk