

MAXIMA GROOVED RECEIVER LINE QUICK DETACH RUGER RINGS - WARNE MFG. COMPANY QD GRL RUGER #1, BLACKHAWK, MINI-14 RINGS 30MM HIGH MATTE

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Quickly Removable QD

Maxima Grooved Receiver Line of scope mounts are designed to fill the need of mounting scopes to rifles with an integrated receiver mounting rail. Because each manufacturer has their own proprietary mounting rail design, each ring model must be machined to exacting tolerances for proper fit and function. The Maxima Grooved Receiver line fulfills that need. The precision CNC machined Warne rings provide unsurpassed strength, durability and quality, and fit a variety of rifle models including Ruger #1, Ruger 77, Mini 14 & 30, and Ruger Blackhawk and Redhawk. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases. After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place.



Attributes

- Name: [WARNE MFG. COMPANY QD GRL RUGER #1, BLACKHAWK, MINI-14 RINGS 30MM HIGH MATTE](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947000054
- Mfr. No.: 15RLM
- Finish: Matte Black
- Height: High
- Scope Tube Diameter: 30mm
- Size: High
- Style: Ruger-Style Rings
- Delivery weight: 0.227kg
- UPC: 656813010639

Item details

Made in USA

Table of Contents

- [Startpage](#)
- [MAXIMA GROOVED RECEIVER LINE QUICK DETACH RUGER RINGS SAFETY INSTRUCTIONS](#)
- [About Us](#)

MAXIMA GROOVED RECEIVER LINE QUICK DETACH RUGER RINGS SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the Maxima Grooved Receiver Line Quick Detach Ruger Rings by Warne Mfg. Company. These scope rings are designed to securely mount optics to rifles equipped with an integrated receiver mounting rail. This guide provides essential safety instructions and installation procedures to ensure the safe and effective use of this product.

General Safety Guidelines

To ensure safe use of the Maxima Grooved Receiver Rings, please adhere to the following guidelines:

- Always inspect the scope rings and rifle before use for any signs of damage or wear.
- Ensure that the rings are compatible with your specific rifle model.
- Follow all manufacturer instructions for installation and usage.
- Use only the recommended scope tube diameter (30mm) for optimal performance.
- Keep the product out of reach of children and vulnerable individuals.
- Report any accidents or unsafe conditions to the appropriate authorities.
- Regularly check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

When using the Maxima Grooved Receiver Rings, please observe the following precautions:

- Ensure that the rings are properly tightened to avoid any movement during use.
- Avoid overtightening the rings, which can damage the scope or rifle.
- Always use the rings in accordance with the intended purpose and specifications.
- Do not modify the rings in any way, as this can compromise safety and performance.
- Be aware of the environmental conditions in which you are using the product, as extreme temperatures or moisture can affect performance.

Instructions for Installation and Usage

To install and use the Maxima Grooved Receiver Rings safely, follow these steps:

1. Preparation:

- Gather all necessary tools for installation, including a torque wrench and appropriate screwdriver.
- Ensure the rifle is unloaded and pointed in a safe direction.

2. Installation:

- Remove the existing scope rings (if applicable).
- Align the Maxima Grooved Receiver Rings with the integrated mounting rail on your rifle.
- Place the scope into the rings, ensuring it is centered.
- Tighten the rings gradually, alternating between each side to maintain even pressure.
- Use a torque wrench to tighten the screws to the manufacturer's recommended specifications.

3. Usage:

- Once installed, check the alignment of the scope and make any necessary adjustments.
- Ensure the lever of the quick detach system is easily accessible for removal and reattachment of

the scope.

- To detach the scope, pull out on the lever, turn it to the desired location, and let it snap back into place.
- After reattaching the scope, confirm that it retains zero before proceeding to use the rifle.

Disposal Instructions

When the Maxima Grooved Receiver Rings reach the end of their life cycle, please dispose of them responsibly:

- Do not dispose of the product in regular household waste.
- Check local regulations for proper disposal methods for metal and plastic components.
- Consider recycling options where available.

Contact Information for Further Support

For any inquiries regarding the Maxima Grooved Receiver Rings, please refer to the manufacturer's contact information provided with the product packaging or on the official website.

By following these safety instructions, you can ensure a safe and enjoyable experience with your Maxima Grooved Receiver Line Quick Detach Ruger Rings. Thank you for your attention to safety and compliance with these guidelines.

About Us

Brownells Europe

Brownells Europe - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

P.O.Box 4300
Warwick
CV34 9BR

www.brownells.eu