

MAXIMA QUICK DETACH RINGS - 34MM LOW (0.25") QD RINGS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired - retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases. After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



Attributes

- Name: [34MM LOW \(0.25"\) QD RINGS BLACK](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947000256
- Mfr. No.: 220LM
- Finish: Matte Blue
- Height: .250"
- Scope Tube Diameter: 34mm
- Size: Low
- Style: Weaver-Style Rings
- Delivery weight: 0.159kg
- Shipping height: 13mm
- Shipping width: 112mm
- Shipping length: 163mm
- UPC: 656813102402

Item details

Made in USA

Table of Contents

- Startpage
- MAXIMA QUICK DETACH RINGS 34MM LOW (0.25") QD RINGS BLACK Safety Instruction Guide
- About Us

MAXIMA QUICK DETACH RINGS 34MM LOW (0.25") QD RINGS BLACK Safety Instruction Guide

Introduction

Thank you for choosing the Maxima Quick Detach Rings. These rings are designed for durability and versatility in mounting your optics securely. This safety instruction guide provides important information on how to use, install, and dispose of the product safely, ensuring compliance with the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure safe use of the product by following all instructions provided.
- Regularly inspect the rings for any signs of wear or damage before each use.
- Use the rings only with compatible scope tubes and bases as specified in the product details.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe conditions or accidents to the appropriate authorities.

Specific Safety Precautions for Use

- Only use the Maxima Quick Detach Rings with Warne bases or compatible Weaver cross slot and MilSpec Picatinny style bases and rails.
- Do not exceed the recommended weight limit for the optics mounted on the rings.
- Ensure that the rings are securely tightened before use to prevent any movement during recoil.
- Avoid using excessive force when tightening the levers to prevent damage to the rings or the base.
- Be cautious of sharp edges on the rings during installation and adjustment.

Instructions for Installation and Usage

1. Installation:

- Select the appropriate Warne base or compatible base for your optics.
- Place the Maxima Quick Detach Rings onto the base, aligning them properly.
- Insert the Torx style T15 socket cap screws into the designated holes and tighten them securely.
- Adjust the lever to the desired position for easy access and operation.

2. Usage:

- To detach the optics, pull out on the lever and turn it to release the rings from the base.
- When reattaching, align the rings with the base and press down until the lever clicks into place, ensuring a secure fit.
- Check the alignment of the scope after reattachment to confirm that it has retained its zero.

3. PostUse Care:

- After each use, inspect the rings for any signs of damage or wear.
- Clean the rings with a soft, dry cloth to remove any dirt or debris.
- Store the rings in a dry place away from moisture and extreme temperatures.

Disposal Instructions

- Dispose of the Maxima Quick Detach Rings in accordance with local regulations.
- Do not dispose of the product in regular household waste.

- Consider recycling the materials if applicable, especially if you are disposing of the rings after use.

Contact Information for Further Support

For any questions or concerns regarding the use and safety of the Maxima Quick Detach Rings, please refer to the manufacturer's contact information included with your product packaging.

Thank you for prioritizing safety and for choosing Maxima products. Your attention to these guidelines ensures a safe and effective experience with your Quick Detach Rings.

About Us

Brownells Česká republika

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.cz