

MAXIMA QUICK DETACH RINGS - 36MM MEDIUM (.375") QD RINGS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired - retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases. After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



Attributes

- Name: [36MM MEDIUM \(.375"\) QD RINGS BLACK](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947000623
- Mfr. No.: 231LM
- Finish: -
- Height: -
- Scope Tube Diameter: -
- Size: -
- Style: -
- Delivery weight: 0.227kg
- Shipping height: 38mm
- Shipping width: 127mm
- Shipping length: 165mm
- UPC: 656813105946

Item details

Made in USA

Table of Contents

- Startpage
- MAXIMA QUICK DETACH RINGS 36MM MEDIUM (.375") QD RINGS BLACK Safety Instruction Guide
- About Us

MAXIMA QUICK DETACH RINGS 36MM MEDIUM (.375") QD RINGS BLACK Safety Instruction Guide

Introduction

Thank you for choosing the Maxima Quick Detach Rings. These rings provide a durable and versatile mounting system for your optics. This safety instruction guide aims to ensure the safe use of this product in compliance with the EU General Product Safety Regulation (GPSR). Please read this guide thoroughly before use.

General Safety Guidelines

- Ensure the product is used only for its intended purpose as a mounting system for scopes.
- Regularly inspect the rings and bases for any signs of wear or damage before each use.
- Keep the product out of reach of children and individuals who may not understand its proper use.
- Be aware of your surroundings while using firearms to prevent accidents.
- Report any unsafe product conditions or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Always confirm that the rings are securely attached to the bases before use.
- Do not exceed the recommended torque settings when tightening screws to avoid damaging the rings or bases.
- Avoid using the rings with incompatible bases or accessories to prevent failure.
- Ensure that the recoil control key is properly engaged to maintain the stability of the rings during use.
- Do not modify or disassemble the rings, as this may compromise safety and performance.
- Use eye protection when mounting or adjusting the scope to prevent injury from potential recoil or parts.

Instructions for Installation and Usage

1. Installation:

- Carefully read the installation manual provided with the mounting system.
- Align the Maxima Quick Detach Rings with the Warne bases or compatible Weaver cross slot and MilSpec Picatinny style bases.
- Securely fasten the rings using the provided Torx style T15 socket cap screws. Ensure they are tightened to the manufacturer's specifications.
- Use the indexable lever system to adjust the lever position for ease of use.
- Confirm that the rings are properly seated and that the recoil control key is engaged.

2. Usage:

- Before each use, check that the scope is securely mounted and that there are no loose components.
- When detaching the scope, pull out on the lever, turn it to the desired location, and let it snap back into place to ensure proper engagement.
- After reattaching the scope, verify that it maintains zero before proceeding with shooting.

Disposal Instructions

- Dispose of the product in accordance with local regulations for metal and electronic waste.
- Do not throw the product in regular household waste.
- If you are unsure about the disposal method, contact your local waste management authority for guidance.

Contact Information for Further Support

For any inquiries regarding safety or product issues, please refer to the manufacturer's contact details provided in the product packaging or visit the official website.

By following these guidelines, you can ensure the safe and effective use of the Maxima Quick Detach Rings. Thank you for your attention to safety.

About Us

Brownells Česká republika

Brownells - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

www.brownells.cz