

# MAXIMA QUICK DETACH RINGS - WARNE MFG. COMPANY 1" HIGH (.525") QD RINGS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

## Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired - retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases.

After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



## Attributes

- Name: [WARNE MFG. COMPANY 1" HIGH \(.525"\) QD RINGS BLACK](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947623200
- Mfr. No.: 202LM
- Finish: Matte Blue
- Height: .525"
- Scope Tube Diameter: 1"
- Size: High
- Style: Weaver-Style Rings
- Delivery weight: 0.159kg
- Shipping height: 24mm
- Shipping width: 110mm
- Shipping length: 144mm
- UPC: 656813000302

## Item details

Made in USA

# Table of Contents

- Startpage
- MAXIMA QUICK DETACH RINGS SAFETY INSTRUCTION GUIDE
- About Us

# MAXIMA QUICK DETACH RINGS SAFETY INSTRUCTION GUIDE

## Introduction

Thank you for choosing the Maxima Quick Detach Rings by Warne MFG. Company. These rings are designed to provide a durable and versatile mounting solution for your optics. To ensure safe and effective use of this product, please read and follow the safety instructions outlined in this guide.

## General Safety Guidelines

- Ensure that the product is used only for its intended purpose as a scope mounting system.
- Regularly inspect the rings for signs of wear or damage before each use.
- Keep the product out of reach of children and vulnerable individuals.
- Follow all installation and usage instructions carefully to avoid accidents.
- Report any unsafe conditions or accidents to the appropriate authorities.

## Specific Safety Precautions for Use

- **Recoil Safety:** The Maxima QD rings are designed to withstand significant recoil. Ensure that they are properly mounted to avoid shifting or movement during use.
- **Installation:** Use only the provided Torx style T15 socket cap screws to secure the rings. Do not substitute with other types of screws.
- **Weight Limitations:** Ensure that the optics mounted on the rings do not exceed the weight limit specified by the manufacturer.
- **Environmental Conditions:** Avoid exposing the rings to extreme temperatures or corrosive environments, as this may affect their performance.

## Instructions for Installation and Usage

### 1. Preparation:

- Gather all necessary tools, including a Torx T15 screwdriver.
- Ensure the mounting surface is clean and free of debris.

### 2. Installation:

- Align the Maxima QD rings with the Warne bases or compatible Weaver cross slot and MilSpec Picatinny style bases.
- Insert the Torx T15 socket cap screws into the designated holes and handtighten to secure the rings in place.
- Use the Torx screwdriver to tighten the screws to the manufacturer's recommended torque specifications.

### 3. Mounting the Optics:

- Place the scope into the rings, ensuring proper alignment.
- Secure the scope by tightening the levers on the Maxima QD rings. Pull out on the lever, turn to the desired location, and let it snap into place.
- Confirm that the scope is securely mounted and that there is no movement when the rifle is handled.

### 4. Post Installation Check:

- Perform a visual inspection to ensure that all screws are tight and the rings are securely mounted.
- Test the scope for zero retention by removing and reattaching it to verify that it maintains accuracy.

## Disposal Instructions

- Dispose of any packaging materials in accordance with local recycling regulations.
- When the product reaches the end of its life, dispose of it responsibly. Check with local authorities for proper disposal methods for metal and plastic components.

## Contact Information for Further Support

For any inquiries regarding safety, installation, or product performance, please reach out to the manufacturer or authorized distributors. Ensure that you have your product details ready for a more efficient response.

Thank you for your attention to these safety instructions. Enjoy using your Maxima Quick Detach Rings safely and effectively!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)