

MAXIMA QUICK DETACH RINGS - WARNE MFG. COMPANY 30MM LOW (0.25") QD RINGS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired - retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases.

After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



Attributes

- Name: [WARNE MFG. COMPANY 30MM LOW \(0.25"\) QD RINGS BLACK](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947630000
- Mfr. No.: 213LM
- Finish: Matte Blue
- Height: .250"
- Scope Tube Diameter: 30mm
- Size: Low
- Style: Weaver-Style Rings
- Delivery weight: 0.159kg
- Shipping height: 25mm
- Shipping width: 109mm
- Shipping length: 142mm
- UPC: 656813000838

Item details

Made in USA

Table of Contents

- Startpage
- MAXIMA QUICK DETACH RINGS Safety Instruction Guide
- About Us

MAXIMA QUICK DETACH RINGS Safety Instruction Guide

Introduction

Thank you for choosing the Maxima Quick Detach Rings by Warne MFG. Company. These rings are designed to provide a durable and versatile mounting solution for your optics. This guide provides essential safety instructions and best practices to ensure safe usage and optimal performance of the product.

General Safety Guidelines

- Always inspect the rings before each use for any signs of damage or wear.
- Ensure that the rings are compatible with your scope and base before installation.
- Do not exceed the manufacturer's recommended torque specifications when tightening screws.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe products or incidents to the appropriate authorities.

Specific Safety Precautions for Use

- **Avoid Misuse:** Do not use the rings for any purpose other than mounting optics.
- **Recoil Management:** Ensure that the recoil control key is properly engaged to prevent movement during firing.
- **Zero Retention:** When detaching and reattaching the optics, verify that zero is maintained before use.
- **Proper Fit:** Ensure that the rings fit securely on the base and around the scope to avoid any accidents.
- **Material Caution:** The rings are made from steel and may have sharp edges. Handle with care to prevent injury.

Instructions for Installation and Usage

1. Compatibility Check:

- Verify that the Maxima Quick Detach Rings are compatible with your scope and base.

2. Installation Steps:

- Place the rings on the scope tube.
- Align the rings with the mounting base.
- Use the Torx style T15 socket cap screws to secure the rings to the base.
- Tighten the screws to the manufacturer's recommended torque specifications to ensure a secure fit.

3. Lever Adjustment:

- After securing the rings, pull out on the lever.
- Rotate the lever to the desired position.
- Release the lever to allow it to snap into place.

4. Optics Attachment:

- To detach the optics, pull out on the lever and rotate it to disengage.
- When reattaching, ensure the rings are properly aligned and the lever is engaged.

5. Post Installation Check:

- After installation, confirm that the scope is level and securely mounted.
- Test the zero by firing a few rounds and making adjustments as necessary.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- Consider recycling the materials if possible.

Contact Information for Further Support

For any inquiries regarding safety or product performance, please refer to the manufacturer's contact details provided with your purchase.

Thank you for choosing the Maxima Quick Detach Rings. Your safety and satisfaction are our priority.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk