

MAXIMA QUICK DETACH RINGS - WARNE MFG. COMPANY 30MM HIGH (.525") QD RINGS BLACK

[Optics & Mounting](#) > [Rings, Mounts & Bases](#) > [Scope Rings](#)

Strong, All-Steel With Adjustable Levers; Fit Weaver-Style Bases

Maxima Quick Detach Rings are the most durable and versatile quick detachable mounting system available. Each ring is precision CNC machined from sintered steel technology, a process that allows intricate steel parts to be formed and then fired - retaining the strength properties of steel while adding the necessary ductility that scope mounts require for perfect grip contact around the circumference of the scope. The Maxima QD rings sport the unique Warne indexable lever system which allows the user to remove the optics from the rifle then reattach it without the loss of zero, as well as allowing the location of the lever to be indexed once the rings are affixed to the bases. After the levers are tightened, simply pull out on the lever, turn it to the desired location then let it snap into place. When used on the all steel Warne Maxima bases, we guarantee accuracy of within 1/1000th of an inch when removing and reattaching the optics. Unique to the industry, the Maxima QD has a square stainless steel recoil control key. This ensures a positive recoil engagement surface across the full width and depth of the recoil slot in the base. The recoil control key guarantees the position of the rings will not shift or move under fierce recoil and also protects against peening or swaging when mounted on aluminum bases. Warne Maxima scope rings are designed to fit Warne bases as well as all Weaver cross slot and Mil-Spec Picatinny style bases and rails. Finally, the Maxima QD rings are finished with either a durable DuPont powder coat in matte or gloss black, or electroless nickel finished for a stainless steel look. Warne Maxima rings are then assembled with 4 quality Torx style T-15 socket cap screws.



Attributes

- Name: [WARNE MFG. COMPANY 30MM HIGH \(.525"\) QD RINGS BLACK](#)
- Manufacturer: [WARNE MFG. COMPANY](#)
- Product no.: 947630200
- Mfr. No.: 215LM
- Finish: Matte Blue
- Height: .525"
- Scope Tube Diameter: 30mm
- Size: High
- Style: Weaver-Style Rings
- Delivery weight: 0.181kg
- Shipping height: 23mm
- Shipping width: 109mm
- Shipping length: 142mm
- UPC: 656813000388

Item details

Made in USA

Table of Contents

- Startpage
- MAXIMA QUICK DETACH RINGS SAFETY INSTRUCTIONS
- About Us

MAXIMA QUICK DETACH RINGS SAFETY INSTRUCTIONS

Introduction

Thank you for choosing the MAXIMA QUICK DETACH RINGS from Warne Mfg. Company. These rings are designed for durability and versatility in mounting scopes securely on your rifle. Please read this safety instruction guide carefully to ensure safe and effective use of the product.

General Safety Guidelines

- Always ensure that the product is used according to the manufacturer's instructions.
- Keep all packaging materials and instructions for future reference.
- Inspect the product regularly for signs of wear or damage.
- Store the product in a safe, dry place away from children and pets.
- Report any unsafe products or incidents to the appropriate authorities.
- Check for recall updates on the EU's Safety Gate platform.

Specific Safety Precautions for Use

- Ensure that the rings are compatible with your scope and rifle before installation.
- Do not exceed the recommended torque specifications when tightening screws.
- Avoid using the rings with damaged or worn components.
- Do not modify the rings or attempt to repair them yourself.
- Always check the mounting system for stability before use.
- Be cautious of sharp edges during installation and handling.

Instructions for Installation and Usage

1. Preparation

- Gather all necessary tools, including a Torx T15 screwdriver.
- Ensure that your rifle is unloaded and pointed in a safe direction.

2. Installation

- Place the Warne Maxima bases onto your rifle.
- Align the Maxima Quick Detach Rings with the bases.
- Insert the Torx T15 socket cap screws into the rings.
- Tighten the screws gradually, ensuring even pressure.
- Verify that the rings are securely fastened and do not shift.

3. Using the Quick Detach Feature

- To detach the scope, pull out on the lever and rotate it to the desired position.
- Ensure that the lever snaps back into place securely.
- To reattach the scope, align it with the rings and press down firmly until the lever engages.

4. PostInstallation Check

- After installation, check that the scope is properly aligned and that the zero is maintained.
- Test the quick detach feature to ensure it functions correctly.

Disposal Instructions

- Dispose of packaging materials responsibly and in accordance with local regulations.
- If the product is no longer usable, dispose of it in a way that prevents environmental harm.
- Follow local waste management guidelines for disposal of metal and plastic components.

Contact Information for Further Support

For additional information or assistance regarding safety concerns, please refer to the manufacturer's website or contact their customer service directly.

Thank you for your attention to these safety instructions. Enjoy your MAXIMA QUICK DETACH RINGS and the enhanced shooting experience they provide.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk