

# LONG RANGE ARMS LRA S90 BRACKET FOR SEND IT MV3 & SPUHR MOUNTS

[Optics & Mounting](#) > [Optic Accessories](#) > [Scope Anti-Cant Devices](#)

Send iT MV3 Level sold separately. LRA S90 Bracket Allows the Send iT MV3 to be mounted directly to Spuhr's SP, SA, SS, and ST models in the vertical Position. Attention! Some mounts may require Spuhr A-0001: Spacer 4mm. Contact your Spuhr dealer for specific applications. Included; LRA S90 Bracket #8-32 screw (1) 4mm x 10mm screws (2) **\*\*Warning\*\*** Screw lengths MUST be checked PRIOR to attaching the mounts. In some applications the screw can "bottom out" against the scope tube or damage other components if the screw length is excessive or the wrong size/thread pitch is used. YOU are RESPONSIBLE to check the length and size of screws and verify interferences before final assembly. LRA is not liable for damage to our products or the products they are being mounted or attached to. Step 1- Attach the LRA S90 to the Spuhr mount using the (2) supplied 4mm x 10mm flat head screws using either an IP20 or T20 Torx Plus or Torx drive. Torque both screws to 20-25 in-lbs. Step 2- attach the Send iT MV3 to the LRA S90 bracket. Follow the instructions included with the Send iT MV3 for removal of the Picatinny mount (link below). Carefully fit the Send iT into the pocket of the LRA S90 bracket by hand and confirm it's sitting flat and fully seated BEFORE installing the screw. Install and torque the (1) supplied # 8-32 Flat head screw to 30-34 in-lbs using a 3/32 Allen drive.

NO IMAGE  
AVAILABLE

## Attributes

- Name: [LONG RANGE ARMS LRA S90 BRACKET FOR SEND IT MV3 & SPUHR MOUNTS](#)
- Manufacturer: [MDT](#)
- Product no.: EU2010214
- Mfr. No.: 107203-BLK
- Finish: Black
- Delivery weight: 0.02kg
- Shipping height: 19mm
- Shipping width: 105mm
- Shipping length: 127mm
- UPC: 682157410316

# Table of Contents

- Startpage
- LONG RANGE ARMS LRA S90 Bracket for Send iT MV3 & Spuhr Mounts Safety Instruction Guide
- About Us

# LONG RANGE ARMS LRA S90 Bracket for Send iT MV3 & Spuhr Mounts Safety Instruction Guide

## Introduction

Thank you for choosing the LONG RANGE ARMS LRA S90 Bracket. This product is designed to securely mount the Send iT MV3 to compatible Spuhr mounts. It is essential to follow the safety instructions and guidelines outlined in this document to ensure safe and effective use.

## General Safety Guidelines

- Ensure safe use of the LRA S90 Bracket by following all instructions carefully.
- Always check for compatibility with your specific Spuhr mount model.
- Inspect all components for damage before installation.
- Keep the product out of reach of children and vulnerable individuals.
- Report any unsafe products or accidents to the appropriate authorities.
- Stay informed about recalls by checking updates on the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- **Screw Length Check:** Always verify screw lengths before attaching the mounts. Using screws that are too long can damage the scope tube or other components.
- **Proper Tools:** Use the recommended tools (IP20 or T20 Torx Plus or Torx drive, and 3/32 Allen drive) for installation to avoid damage.
- **Torque Specifications:** Adhere to the specified torque values for all screws to prevent overtightening, which can lead to damage.
- **Installation Surface:** Ensure that the installation surface is stable and free from obstructions.
- **Flat Seating:** Confirm that the Send iT MV3 is seated flat and fully before securing it with screws.

## Instructions for Installation and Usage

### 1. Attach the LRA S90 to the Spuhr Mount:

- Use the (2) supplied 4mm x 10mm flat head screws.
- Tighten both screws to a torque of 2025 inlbs using an IP20 or T20 Torx Plus or Torx drive.

### 2. Attach the Send iT MV3 to the LRA S90 Bracket:

- Follow the instructions provided with the Send iT MV3 for removal of the Picatinny mount.
- Carefully fit the Send iT into the pocket of the LRA S90 bracket by hand.
- Ensure that the Send iT is sitting flat and fully seated BEFORE installing the screw.
- Install and torque the (1) supplied #832 flat head screw to 3034 inlbs using a 3/32 Allen drive.

### 3. Final Check:

- After installation, doublecheck all screws and connections to ensure everything is secure and properly installed.

## **Disposal Instructions**

- Dispose of the LRA S90 Bracket and any packaging materials in accordance with local regulations.
- Do not dispose of the product in regular household waste. Instead, use designated recycling facilities where available.

## **Contact Information for Further Support**

For any questions or concerns regarding the use or safety of the LONG RANGE ARMS LRA S90 Bracket, please consult your local Spuhr dealer or authorized retailer for assistance.

By following these guidelines, you can ensure a safe and effective experience with your LONG RANGE ARMS LRA S90 Bracket. Thank you for your attention to safety and proper usage.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)