

XRS TIKKA T3 LH - MDT XRS CHASSIS Tikka T3 LH

[Rifle Parts](#) > [Stock Parts](#) > [Rifle Stocks](#)

The XRS Chassis is designed for shooters that want the fit and feel of a traditional shaped rifle stock with the benefits of a modern precision rifle chassis system. Each XRS Chassis is constructed from a full-length CNC machined core of 6061 aircraft grade aluminum wearing high strength textured polymer panels for insulation from the elements. The precision aluminum V-block bedding system ensures fit and function to maximize the accuracy of any rifle action. The XRS Chassis features a replaceable over molded and textured grip system, with both an angled grip and a vertical grip included in box.

The XRS Chassis is the most advanced and configurable crossover stock on the market and is the ideal performance upgrade for any factory rifle or foundation for a custom rifle build. Weighing in at 1,7kg (depending on inlet), the XRS is ideal for both hunting or target rifles. The XRS features adjustable length of pull via spacers from 13.25" to 15+" and a quick adjust cheek piece to adjust for scope height over bore. The XRS accepts standard AICS pattern magazines and has an easy to manipulate ambidextrous magazine latch. The generous 12" long Forend comes with M-LOK slots built in for accessory mounting and attachment of ARCA or picatinny rails.

NO IMAGE
AVAILABLE

Specifications

Length

- 32.25" chassis system

Weight

- Starting at 1,7kg
- (Depending on rifle model)

Grip Compatibility

- Compatible only with the included vertical and angled grips

Attributes

- Name: [MDT XRS CHASSIS Tikka T3 LH](#)
- Manufacturer: [MDT](#)
- Product no.: EU2011638
- Mfr. No.: 104935-FDE
- Action Type: Short
- Colour: FDE
- Hand: Left
- Hand (RH LH): Left
- Material: 6061 Aluminum
- Model: T3
- Style: Chassis
- Weapon type: Tikka

- Delivery weight: 2.33kg
- Shipping height: 70mm
- Shipping width: 184mm
- Shipping length: 908mm
- UPC: 682157407873

Table of Contents

- Startpage
- Safety Instructions for MDT XRS TIKKA T3 LH Chassis
- About Us

Safety Instructions for MDT XRS TIKKA T3 LH Chassis

Introduction

Thank you for choosing the MDT XRS TIKKA T3 LH Chassis. This product is designed to enhance your shooting experience while ensuring safety and performance. Please read this safety instruction guide carefully to understand how to use the chassis safely and effectively.

General Safety Guidelines

- Always ensure that your rifle is unloaded before installing or adjusting the chassis.
- Inspect the chassis for any damage before use. Do not use if damaged.
- Keep the chassis out of reach of children and unauthorized users.
- Always handle firearms responsibly and in accordance with local laws and regulations.
- Use only compatible accessories and components as specified in this guide.
- Be aware of your surroundings and ensure a safe shooting environment.
- Regularly check for recalls or safety alerts regarding this product on the EU Safety Gate platform.

Specific Safety Precautions for Use

• Hazard Identification:

- Improper installation may lead to firearm malfunction.
- Inadequate grip may result in loss of control during firing.
- Using incompatible magazines may cause feeding issues.

• Avoiding Hazards:

- Follow installation instructions carefully to ensure proper fit.
- Always use the provided vertical and angled grips for optimal control.
- Ensure that only AICS pattern magazines are used with this chassis.
- Regularly inspect all components for wear or damage.

• Agespecific Warnings:

- This product is intended for adult users only. Ensure that minors are supervised when handling firearms or related equipment.

Instructions for Installation and Usage

1. Installation:

- Remove the existing stock from your Tikka T3 LH rifle.
- Align the action of the rifle with the Vblock bedding system of the XRS Chassis.
- Securely attach the rifle action to the chassis using the provided screws.
- Ensure that the chassis is firmly attached and that there are no gaps.

2. Grip Installation:

- Choose between the vertical or angled grip included in the box.
- Align the grip with the designated slots on the chassis.
- Secure the grip using the provided screws.

3. Adjusting Length of Pull:

- Use the spacers included to adjust the length of pull from 13.25" to 15".
- Ensure that the adjustment is secure before use.

4. Cheek Piece Adjustment:

- Adjust the cheek piece for optimal scope height over bore.
- Ensure that the cheek piece is locked in place before firing.

5. Magazine Loading:

- Insert AICS pattern magazines into the chassis.
- Ensure that the magazine latch is functioning properly and is easy to manipulate.

6. Accessory Mounting:

- Use the builtin MLOK slots for mounting accessories.
- Ensure that all mounted accessories are secure and do not interfere with the operation of the chassis.

Disposal Instructions

- Dispose of the chassis according to local regulations.
- Do not dispose of in regular household waste.
- Consider recycling options for aluminum and polymer materials.

Contact Information for Further Support

For any questions or concerns regarding the MDT XRS TIKKA T3 LH Chassis, please refer to the manufacturer's website or contact your local distributor. It is important to have a reliable point of contact for safety inquiries and product support.

By following these safety instructions, you can ensure a safe and enjoyable experience with your MDT XRS TIKKA T3 LH Chassis. Always prioritize safety and responsible firearm handling.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk