

3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP P4FL 1cm ccw DT35 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [3-20x50 PM II Ultra Short LP P4FL 1cm ccw DT35 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015772
- Mfr. No.: 667-911-972-F1-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537010459

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for the 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope by Schmidt and Bender. This highperformance riflescope is designed for serious shooters who require precision and clarity across various distances. To ensure safe and effective use of this product, please read and follow these safety instructions carefully.

General Safety Guidelines

- Always treat the riflescope as if it is loaded, even when not in use.
- Keep the riflescope out of reach of children and unauthorized users.
- Use the riflescope only for its intended purpose, which is to enhance shooting accuracy.
- Inspect the riflescope regularly for any signs of damage or wear.
- Avoid using the riflescope in extreme weather conditions that may affect performance.
- Ensure that the riflescope is mounted securely to your firearm before use.
- Do not attempt to disassemble or modify the riflescope.

Specific Safety Precautions for Use

- **Magnification and Field of View:** Be aware of the magnification range (3-20x) and field of view (approx. 13.0-2.1 m @ 100 m) while using the riflescope. Adjust the magnification according to your shooting distance and environment.
- **Eye Relief:** Maintain a proper distance of approximately 90 mm from the eyepiece to avoid injury from recoil.
- **Parallax Adjustment:** Use the side parallax adjustment feature to enhance accuracy, especially at varying distances (from approx. 25 m to infinity).
- **Illuminated Reticle:** When using the illuminated reticle, ensure that the brightness is set to a comfortable level to avoid eye strain.
- **Light Conditions:** The riflescope performs optimally in various light conditions. However, avoid using it in complete darkness without proper illumination.
- **Rugged Use:** The riflescope is designed for rugged use. However, avoid dropping or subjecting it to excessive shock.

Instructions for Installation and Usage

Installation

1. Mounting the Riflescope:

- Ensure that the firearm is unloaded.
- Select a suitable mounting base compatible with the 34 mm main tube diameter.
- Securely attach the riflescope to the mounting base using the provided rings and screws.
- Check that the riflescope is level and aligned with the barrel.

2. Zeroing the Riflescope:

- After mounting, zero the riflescope according to the manufacturer's instructions.
- Adjust the windage and elevation turrets to align the reticle with the point of impact.

Usage

- **Adjusting Magnification:** Rotate the magnification ring to select the desired level of magnification based on your shooting distance.
- **Parallax Adjustment:** Use the side parallax adjustment knob to eliminate parallax error for improved accuracy.
- **Reticle Illumination:** Activate the illuminated reticle using the designated control, adjusting brightness as needed.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste and optical devices.
- Do not dispose of the riflescope in regular household waste.
- Consider recycling options if available in your area.

Contact Information for Further Support

For any inquiries or concerns regarding the safety or performance of the 3-20x50 PM II Ultra Short Riflescope, please refer to the manufacturer's contact information included in the product packaging or visit their official website for more information.

By following these safety instructions, you can ensure the safe and effective use of your 3-20x50 PM II Ultra Short Riflescope. Always prioritize safety and responsible usage. Thank you for your attention to these guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk