

3-20x50 PM II Ultra Short - 3-20x50 PM II Ultra Short LP GR²ID 1cm cw DT35 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 3-20×50 PM II Ultra Short from Schmidt and Bender is a compact yet powerful riflescope engineered for high-performance engagements across medium to long distances. With its 3–20× magnification range and a 50 mm objective lens, it offers outstanding optical clarity and flexibility in a streamlined form factor.

Constructed around a robust 34 mm main tube, it maintains a length of approximately 340 mm and weighs around 900 g, striking an excellent balance between size and performance—ideal for mounting on compact platforms without compromising optics.

Its field of view spans roughly 13.0–2.1 m at 100 m, providing broad situational awareness at lower magnification and refined detail at the high end. The exit pupil ranges around 11.4–2.5 mm, and the eye relief is approximately 90 mm, supporting comfortable shooting in varied positions while maintaining strong light-gathering even as light fades.

Advanced features include first focal plane (FFP) illuminated reticle options, side parallax adjustment (from approx. 25 m to infinity), and a low-profile elevation turret optimized for tactical precision.

Key Specifications:

Magnification: 3–20×
Objective Lens Diameter: 50 mm
Main Tube Diameter: 34 mm
Field of View: approx. 13.0–2.1 m @100 m
Exit Pupil: approx. 11.4–2.5 mm
Eye Relief: approx. 90 mm
Length: approx. 340 mm
Weight: approx. 900 g

With precision optics, compact build, and rugged mechanical design, the 3-20×50 PM II Ultra Short is built for serious shooters who demand premium performance in a versatile package.

Attributes

- Name: [3-20x50 PM II Ultra Short LP GR²ID 1cm cw DT35 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015790
- Mfr. No.: 667-945-422-F2-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm
- EAN: 4060537064520

NO IMAGE
AVAILABLE

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 3-20x50 PM II Ultra Short Riflescope](#)
- [About Us](#)

Safety Instruction Guide for 3-20x50 PM II Ultra Short Riflescope

Introduction

Thank you for choosing the 3-20x50 PM II Ultra Short Riflescope from Schmidt and Bender. This guide provides essential safety instructions to ensure safe and effective use of the product. Please read this guide carefully before using the riflescope to minimize risks and enhance your shooting experience.

General Safety Guidelines

- Always treat the riflescope as if it is loaded.
- Ensure that the riflescope is used only for its intended purpose.
- Keep the riflescope out of reach of children and unauthorized users.
- Regularly inspect the riflescope for any signs of damage or wear.
- Do not attempt to disassemble or modify the riflescope.
- Always use the riflescope in a safe environment, free from distractions and hazards.
- Be aware of your surroundings and ensure a clear line of sight before firing.
- Follow all local laws and regulations regarding the use of riflescopes and firearms.

Specific Safety Precautions for Use

- Ensure the riflescope is securely mounted to the firearm before use.
- Adjust the magnification and focus settings only when the firearm is pointed in a safe direction.
- Use protective eyewear when shooting to safeguard against recoil and debris.
- Be cautious of the exit pupil size; improper alignment can cause discomfort or hinder vision.
- Maintain a proper shooting posture to ensure stability and control while aiming.
- Avoid using the riflescope in extreme weather conditions that may impair visibility or functionality.
- Do not leave the riflescope unattended in environments where it may be subjected to physical damage or theft.

Instructions for Installation and Usage

• Installation:

1. Ensure the firearm is unloaded and pointed in a safe direction.
2. Use the provided mounting rings to securely attach the riflescope to the firearm's rail.
3. Tighten the mounting screws according to the manufacturer's specifications to avoid loosening during use.
4. Confirm that the riflescope is aligned properly with the firearm's barrel.

• Usage:

1. Adjust the magnification by rotating the magnification ring to the desired level (3x to 20x).
2. Use the side parallax adjustment to refine your focus based on the distance of the target.
3. Ensure the illuminated reticle is activated if needed for lowlight conditions.
4. Before shooting, check the eye relief to ensure a safe distance from the ocular lens to avoid injury.
5. After use, clean the lenses with a soft cloth to maintain optical clarity.

Disposal Instructions

- Dispose of the riflescope in accordance with local regulations regarding electronic waste.
- Do not throw the riflescope in regular trash.

- Contact your local waste management authority for information on proper disposal methods.

Contact Information for Further Support

For any safety inquiries or assistance regarding the 3-20x50 PM II Ultra Short Riflescope, please refer to the product packaging or the manufacturer's website for EUbased contact information.

Conclusion

Following these safety instructions will help ensure a positive experience with your 3-20x50 PM II Ultra Short Riflescope. Always prioritize safety and be aware of your responsibilities as a firearm user. Thank you for choosing Schmidt and Bender.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk