

5-25x56 PM II - 5-25x56 PM II LP P5FL 1cm cw DT / ST

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~ 10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP P5FL 1cm cw DT / ST](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015827
- Mfr. No.: 689-911-622-94-67
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm

NO IMAGE
AVAILABLE

- EAN: 4060537065282

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II Tactical Scope](#)
- [About Us](#)

Safety Instruction Guide for the 5-25x56 PM II Tactical Scope

Introduction

Thank you for choosing the 5-25x56 PM II Tactical Scope from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure the safe and effective use of your product. Please read this document carefully to understand how to handle, install, and maintain your scope while adhering to the EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure safe use of the scope by following all instructions provided in this guide.
- Be aware of potential hazards associated with the product, including but not limited to:
 - Eye strain from prolonged use.
 - Improper mounting leading to scope misalignment.
- Always use the scope in a safe environment, away from children and vulnerable individuals.
- If you suspect any defect or damage, refrain from using the scope and contact a qualified professional.

Specific Safety Precautions for Use

- Always wear appropriate eye protection when using the scope, especially during shooting activities.
- Ensure the scope is securely mounted on your rifle to prevent accidents.
- Avoid using the scope in extreme weather conditions unless it is specifically designed for such use.
- Do not look directly at the sun or other bright light sources through the scope.
- Regularly inspect the scope for any signs of damage or wear, and perform necessary maintenance.

Instructions for Installation and Usage

Installation

1. **Choose the Right Mount:** Select a compatible mounting system for your rifle that can support the 34 mm main tube diameter.
2. **Secure the Mount:** Follow the manufacturer's instructions to securely attach the mount to your rifle.
3. **Align the Scope:** Position the scope in the mount and ensure it is level and properly aligned with the rifle's barrel.
4. **Tighten the Screws:** Carefully tighten all screws on the mount to secure the scope in place, ensuring it is stable and will not shift during use.
5. **Check for Functionality:** Before heading to the range, verify that all adjustments (elevation, windage, and parallax) function correctly.

Usage

1. **Adjusting Magnification:** Use the magnification ring to set your desired zoom level between 5x and 25x.
2. **Focusing the Reticle:** Adjust the diopter to ensure the reticle is sharp and clear.
3. **Setting Parallax:** Adjust the parallax setting according to your shooting distance, ensuring accurate focus.
4. **Taking Aim:** Use the reticle for aiming and make necessary adjustments to windage and elevation based on your shooting conditions.
5. **Maintaining Eye Relief:** Ensure proper eye relief to prevent recoil injuries. Maintain a distance of approximately 90 mm from the eyepiece.

Disposal Instructions

- Dispose of the scope and its components in accordance with local regulations for electronic waste.
- Do not dispose of the product in regular household waste.
- If the scope is damaged beyond repair, consult local waste management authorities for proper disposal methods.

Contact Information for Further Support

For any safety inquiries or further information regarding your 5-25x56 PM II Tactical Scope, please refer to the manufacturer's website or contact their customer support directly.

By following these safety instructions and guidelines, you can ensure a safer experience while using your 5-25x56 PM II Tactical Scope. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk