

5-25x56 PM II - 5-25x56 PM II LP P4FL 1cm cw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP P4FL 1cm cw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015830
- Mfr. No.: 689-911-972-G9-E9
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065367

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This product is designed for precision and reliability in tactical optics. It is essential to understand and follow the safety guidelines outlined in this document to ensure safe and effective use of the product.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose as a tactical scope.
- Always handle the scope with care to avoid damage.
- Keep the product away from children and unauthorized users.
- Regularly check for any signs of damage or wear before use.
- Report any unsafe conditions or accidents to the relevant authorities.

Specific Safety Precautions for Use

- Avoid exposing the scope to extreme temperatures or harsh environmental conditions, which may affect its performance.
- Do not attempt to disassemble or modify the scope, as this may void the warranty and compromise safety.
- Use only compatible mounting systems to ensure proper installation and stability.
- Always ensure that the scope is securely mounted before use to prevent accidents.
- When adjusting the settings, do so gently to avoid damaging the internal components.
- Be aware of your surroundings while using the scope, especially in crowded or confined spaces.

Instructions for Installation and Usage

1. Installation

- Select a suitable mounting location on your firearm.
- Ensure the mounting surface is clean and free of debris.
- Attach the scope using compatible rings and bases; follow the manufacturer's instructions for secure installation.
- Check that the scope is level and aligned with the firearm's barrel.

2. Usage

- Adjust the magnification by rotating the zoom ring smoothly.
- Use the parallax adjustment to ensure a clear image at your target distance.
- Maintain a proper eye relief by positioning your eye at a safe distance from the eyepiece.
- Regularly check the reticle and ensure it remains clear and functional.
- After use, cover the scope with a lens cap to protect it from dust and scratches.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in household waste.
- Take the product to a designated electronic waste recycling facility or follow local guidelines for hazardous waste disposal.

Contact Information for Further Support

For any safety inquiries or additional support, please refer to the appropriate contact resources provided by the manufacturer. Ensure you have your product details ready for efficient assistance.

By following these safety instructions, you can ensure a safe and effective experience with your 5-25x56 PM II. Thank you for your attention to safety.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk