

5-25x56 PM II - 5-25x56 PM II LP P4FL 1cm cw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP P4FL 1cm cw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015834
- Mfr. No.: 689-911-972-L8-I6
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537033571

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe use and enjoyment of your product. Please read this document carefully and keep it for future reference.

General Safety Guidelines

- Always handle the scope with care to avoid damage.
- Ensure that the product is used only for its intended purpose as outlined in this guide.
- Keep the scope out of reach of children and vulnerable individuals to prevent accidents.
- Regularly inspect the scope for any signs of damage or wear. If any issues are found, cease use immediately and consult a professional.
- Be aware of your surroundings when using the scope to avoid accidents or injuries.
- Follow all local laws and regulations regarding the use of optical devices.

Specific Safety Precautions for Use

- **Magnification and Clarity:** Use the magnification settings responsibly to maintain a clear field of view. Avoid using the scope in conditions that may impair visibility.
- **Parallax Adjustment:** Ensure the parallax is adjusted correctly for the distance at which you are shooting to avoid misalignment.
- **Eye Relief:** Maintain an appropriate distance from the eyepiece to prevent eye strain or injury. The recommended eye relief is approximately 90 mm.
- **Weather Conditions:** Since the scope is nitrogenfilled and waterproof, it can be used in various weather conditions. However, avoid exposing it to extreme conditions that could lead to malfunction.
- **Mounting:** Ensure that the scope is securely mounted on your firearm according to the manufacturer's instructions to avoid accidents during use.

Instructions for Installation and Usage

1. Mounting the Scope:

- Select a suitable mounting base that is compatible with the 34 mm main tube.
- Securely attach the scope to the firearm, ensuring it is level and properly aligned.
- Tighten all mounting screws to the manufacturer's specifications.

2. Adjusting the Scope:

- Use the elevation and windage turrets to make adjustments. Each click corresponds to approximately 0.1 mrad (≈ 1 cm at 100 m).
- Adjust the parallax setting based on the distance to the target, ranging from approximately 10 m to infinity.

3. Using the Scope:

- Adjust the magnification from 5x to 25x as needed.
- Always check the field of view (approx. 5.3-1.5 m at 100 m) before aiming.
- Maintain a proper shooting stance and ensure that your firearm is pointed in a safe direction.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic waste and optical devices.
- Do not dispose of the scope in regular household waste. Check for local recycling programs or hazardous waste disposal facilities.

Contact Information for Further Support

For any safety inquiries or concerns regarding the 5-25x56 PM II, please refer to the contact details provided by the manufacturer or retailer from whom you purchased the product. Always ensure that you are using the most current and accurate information available.

By following these safety instructions, you can ensure a safe and enjoyable experience with your 5-25x56 PM II scope. Thank you for your attention to safety!

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk