

# 5-25x56 PM II - 5-25x56 PM II LP P5FL 1cm cw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad ( $\approx 1$  cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×  
Objective Lens Diameter: 56 mm  
Main Tube Diameter: 34 mm  
Field of View: approx. 5.3-1.5 m @100 m  
Exit Pupil: approx. 11.0-2.3 mm  
Eye Relief: approx. 90 mm  
Parallax Adjustment: from ~10 m to infinity  
Click Value: approx. 0.1 mrad ( $\approx 1$  cm at 100 m)  
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

## Attributes

- Name: [5-25x56 PM II LP P5FL 1cm cw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015835
- Mfr. No.: 689-911-622-L8-I6
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE  
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065800

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II](#)
- [About Us](#)

# Safety Instruction Guide for the 5-25x56 PM II

## Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This highperformance tactical scope is designed for precision shooting and demanding conditions. To ensure your safety and the optimal performance of this product, please read and follow the safety instructions outlined in this guide.

## General Safety Guidelines

- **Product Safety:** This scope is designed for safe use. Always follow the instructions provided to minimize risks.
- **Enhanced Recalls:** In the unlikely event of a safety recall, standardized notices will be issued. Always check for updates regarding your product.
- **Online Shopping:** When purchasing online, ensure that the retailer complies with safety regulations.
- **Special Consumer Focus:** Extra precautions should be taken when the product is used by vulnerable groups, including children.
- **EU Contact Point:** For safety inquiries, please refer to the contact information provided by your retailer.
- **Rapid Alerts:** Stay informed about product safety updates through the EU's Safety Gate platform.

## Specific Safety Precautions for Use

- **Age Restrictions:** This product is intended for adult users. It should not be used by children without adult supervision.
- **Eye Protection:** Always wear appropriate eye protection when using this scope to prevent injury from debris.
- **Handling:** Handle the scope with care. Avoid dropping or subjecting it to strong impacts.
- **Environmental Conditions:** Use the scope within the specified environmental conditions to maintain its performance and reliability.
- **Maintenance:** Regularly inspect the scope for signs of damage or wear. Do not use if damaged.

## Instructions for Installation and Usage

### 1. Installation:

- Ensure the firearm is unloaded and pointed in a safe direction before installing the scope.
- Use the provided mounting rings to securely attach the scope to the firearm's rail.
- Tighten the mounting screws evenly to avoid misalignment.

### 2. Usage:

- Adjust the magnification by rotating the zoom ring to your desired setting (5-25x).
- Use the parallax adjustment to focus the reticle at various distances (10 m to infinity).
- Make adjustments using the turret system for windage and elevation as needed. Each click is approximately 0.1 mrad.
- Maintain a proper eye relief distance of approximately 90 mm for optimal viewing.

### 3. Care and Maintenance:

- Clean the lens with a soft, lintfree cloth. Avoid using harsh chemicals.
- Store the scope in a dry, cool place when not in use.
- Ensure the scope is capped or covered to protect it from dust and moisture.

## **Disposal Instructions**

- When disposing of the product, follow local regulations for electronic waste and hazardous materials.
- Remove batteries if applicable and recycle them according to local guidelines.
- Do not dispose of the scope in regular household waste.

## **Contact Information for Further Support**

For additional support, please refer to the contact details provided by your retailer or manufacturer. Ensure you have your product information ready for any inquiries.

By following these safety guidelines and instructions, you can ensure a safe and effective experience with your 5-25x56 PM II scope. Thank you for your attention to these important safety measures.

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)