

5-25x56 PM II - 5-25x56 PM II LP P4FL 1cm ccw DT / ST

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~ 10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP P4FL 1cm ccw DT / ST](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015838
- Mfr. No.: 689-911-972-90-68
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm

NO IMAGE
AVAILABLE

- EAN: 4060537065220

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-25x56 PM II Rifle Scope](#)
- [About Us](#)

Safety Instruction Guide for 5-25x56 PM II Rifle Scope

Introduction

Thank you for choosing the 5-25x56 PM II Rifle Scope from Schmidt and Bender. This guide provides essential safety instructions and usage guidelines to ensure safe and effective operation of your scope. Please read this guide thoroughly before use to maximize safety and performance.

General Safety Guidelines

- **Product Safety:** Always ensure the safe use of the rifle scope. Follow all instructions provided in this manual.
- **Enhanced Recalls:** Stay informed about any recalls or safety notices related to this product. Check the official channels for updates.
- **Online Shopping:** If purchased online, ensure that the platform complies with safety regulations.
- **Special Consumer Focus:** This product is intended for adult users. Keep it out of reach of children to avoid accidental misuse.
- **EU Contact Point:** For any safety inquiries, refer to the designated EU contact point provided by the manufacturer.
- **Rapid Alerts:** Be aware of the Safety Gate system for updates on unsafe products.

Specific Safety Precautions for Use

- **Handling:** Handle the scope with care. Avoid dropping or striking it against hard surfaces.
- **Mounting:** Ensure the scope is securely mounted to the rifle to prevent accidents during use.
- **Adjustment:** Make adjustments to the scope only when it is not in use to prevent accidental discharge of the firearm.
- **Environmental Conditions:** Use the scope in appropriate weather conditions. Avoid exposing it to extreme temperatures or moisture.
- **Cleaning:** Use a soft, lintfree cloth for cleaning the lenses. Avoid using harsh chemicals or abrasive materials.

Instructions for Installation and Usage

Installation

1. Mounting the Scope:

- Select a suitable mounting base for your rifle.
- Align the scope with the mounting rings and secure it tightly.
- Ensure the reticle is level before tightening the rings completely.

2. Initial Setup:

- Before using the scope, check that all adjustments are functioning correctly.
- Set the parallax adjustment to the appropriate distance for your shooting scenario.

Usage

1. Adjusting Magnification:

- Rotate the magnification ring to select the desired zoom level between 5x and 25x.

2. **Focusing the Reticle:**

- Adjust the eyepiece to achieve a clear view of the reticle.

3. **Zeroing the Scope:**

- Follow standard procedures to zero the scope before use. This ensures accuracy at the desired distance.

4. **Using the Turret System:**

- Make elevation and windage adjustments using the turret system. Each click corresponds to 0.1 mrad (approximately 1 cm at 100 m).

5. **Parallax Adjustment:**

- Adjust the parallax setting based on the distance to your target, ensuring a clear image.

Disposal Instructions

- **Environmental Responsibility:** Dispose of the scope in accordance with local regulations. Do not dispose of it with regular household waste.
- **Recycling:** If possible, recycle components of the scope to minimize environmental impact.

Contact Information for Further Support

For further assistance or inquiries regarding the 5-25x56 PM II Rifle Scope, please refer to the manufacturer's official support channels. Ensure you have the product details handy for any support requests.

By following these guidelines, you can ensure the safe and effective use of your 5-25x56 PM II Rifle Scope. Thank you for your attention to these important safety instructions.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk