

5-25x56 PM II - 5-25x56 PM II LP P5FL 1cm ccw DT / ST

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~ 10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP P5FL 1cm ccw DT / ST](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015839
- Mfr. No.: 689-911-622-90-68
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm

NO IMAGE
AVAILABLE

- EAN: 4060537065213

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for the 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This product is designed for longrange precision shooting and is built to the highest standards of quality and reliability. To ensure your safety and the optimal performance of this optical device, please read and follow the safety instructions outlined in this guide.

General Safety Guidelines

- Ensure safe use of the product by following all instructions provided in this guide.
- Be aware of potential hazards associated with the use of optical devices, including but not limited to:
 - Eye strain or discomfort from prolonged use.
 - Risk of damage to the product if used inappropriately.
- Always handle the scope with care to avoid drops or impacts that could affect its performance.
- Keep the product out of reach of children and vulnerable individuals to prevent accidents.

Specific Safety Precautions for Use

- Always use the scope in accordance with the manufacturer's instructions.
- Avoid looking directly at the sun through the scope, as this can cause serious eye damage.
- Ensure that the scope is securely mounted to your rifle before use to prevent accidents.
- Regularly inspect the scope for any signs of damage or wear. If any issues are detected, discontinue use immediately and consult a professional.
- Use protective lens covers when the scope is not in use to prevent dust and scratches.

Instructions for Installation and Usage

1. Installation

- Select a compatible rifle to mount the scope.
- Use appropriate mounting rings to secure the scope to the rifle's rail.
- Ensure that the scope is level and aligned with the rifle's barrel.
- Tighten the mounting screws securely, but be careful not to overtighten.

2. Usage

- Adjust the magnification by rotating the zoom ring to achieve the desired level of magnification.
- Use the parallax adjustment to focus on your target accurately.
- Familiarize yourself with the turret system for windage and elevation adjustments.
- Always ensure a proper shooting stance and maintain control of the rifle while aiming.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic waste.
- Do not dispose of the product in regular household waste.
- If the product is no longer functional or needed, consider recycling options that comply with environmental standards.

Contact Information for Further Support

- For any safety inquiries or further assistance, please contact the manufacturer or your local retailer. Ensure that you have the product details available for reference.

By following these guidelines and instructions, you can ensure the safe and effective use of the 5-25x56 PM II. Thank you for your attention to safety, and enjoy your shooting experience with this premium optical device.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk