

5-25x56 PM II - 5-25x56 PM II LP MSR2 1cm ccw DT / ST

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~ 10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP MSR2 1cm ccw DT / ST](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015840
- Mfr. No.: 689-911-812-90-68
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm

NO IMAGE
AVAILABLE

- EAN: 4060537065206

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This guide provides important safety instructions and guidelines to ensure safe and effective use of your tactical optic. Please read this document carefully to understand how to operate and maintain your product in compliance with EU General Product Safety Regulation (GPSR).

General Safety Guidelines

- Ensure that the product is used only for its intended purpose as a tactical optic.
- Always handle the scope with care to avoid damage.
- Keep the product out of reach of children and vulnerable individuals to prevent accidents.
- Regularly check for any signs of wear or damage before use.
- If the product is damaged or malfunctioning, cease use immediately and seek assistance.

Specific Safety Precautions for Use

- **Avoid Direct Sunlight:** Do not point the scope directly at the sun or any bright light source, as this may damage the internal components.
- **Secure Mounting:** Ensure that the scope is securely mounted to the rifle to prevent movement during use, which could lead to inaccurate shooting.
- **Proper Eye Relief:** Maintain the recommended eye relief of approximately 90 mm to avoid injury from recoil.
- **Parallax Adjustment:** Adjust the parallax setting according to the distance of your target to ensure clarity and accuracy.
- **Environmental Conditions:** Use the scope in suitable weather conditions. Although it is fog and waterproof, extreme temperatures or conditions may affect performance.

Instructions for Installation and Usage

1. Installation:

- Select a compatible rifle mount for the 34 mm main tube diameter.
- Securely attach the scope to the rifle according to the manufacturer's instructions for the mount.
- Ensure that the scope is level and properly aligned with the rifle barrel.

2. Usage:

- Before use, adjust the magnification to your desired level within the 5-25x range.
- Check the field of view, which spans approximately 5.3-1.5 m at 100 m.
- Use the turret system for adjustments:
 - Elevation turret: Doubleturn for elevation adjustments.
 - Windage turret: Singleturn for windage adjustments.
- Regularly verify the optical transmission, which exceeds 90 %, for clarity.
- Adjust the parallax from approximately 10 m to infinity for precise focusing.

Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic waste.
- Do not dispose of the product in regular household waste.
- Consider recycling options available in your area to minimize environmental impact.

Contact Information for Further Support

For any safety inquiries or further assistance, please refer to the appropriate EUbased contact point or retailer from whom you purchased the product. Always ensure that you have the product model and serial number ready for efficient support.

By following these safety instructions and guidelines, you can ensure a safe and enjoyable experience with your 5-25x56 PM II scope. Thank you for your attention to these important details.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk