

5-25x56 PM II - 5-25x56 PM II LP TREMOR3 1cm ccw DT / ST

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~ 10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP TREMOR3 1cm ccw DT / ST](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015841
- Mfr. No.: 689-911-552-90-68
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm
- Shipping length: 450mm

NO IMAGE
AVAILABLE

- EAN: 4060537065183

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for the 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This product is designed for longrange precision and professionallevel reliability. To ensure safe and effective use of this tactical optic, please read and follow the safety instructions outlined in this guide.

General Safety Guidelines

- **Product Safety:** Always ensure that the product is used as intended to avoid risks associated with misuse.
- **Enhanced Recalls:** Stay informed about any product recalls. If you receive a recall notice, follow the instructions provided.
- **Online Shopping:** If purchased online, ensure that the seller complies with safety requirements similar to physical stores.
- **Special Consumer Focus:** Keep this product out of reach of children to prevent accidents.
- **EU Contact Point:** For any safety inquiries, refer to the contact information provided by the retailer or manufacturer.
- **Rapid Alerts:** Regularly check the EU Safety Gate platform for updates on product safety.

Specific Safety Precautions for Use

- **Handling:** Always handle the scope with care. Avoid dropping or subjecting it to strong impacts.
- **Mounting:** Ensure that the scope is securely mounted to the rifle to prevent it from becoming loose during use.
- **Weather Conditions:** Avoid using the scope in extreme weather conditions unless it is specifically designed for such use.
- **Eye Protection:** Always wear appropriate eye protection when using firearms equipped with this scope.
- **Maintenance:** Regularly inspect the scope for any signs of damage or wear. Do not use if damaged.

Instructions for Installation and Usage

1. Installation:

- Ensure the rifle is unloaded before installation.
- Use the appropriate mounting rings compatible with the 34 mm main tube.
- Securely attach the scope to the rifle's mounting base, ensuring it is level and properly aligned.
- Tighten the mounting screws evenly to avoid misalignment.

2. Usage:

- Before using the scope, familiarize yourself with the reticle and turret adjustments.
- Adjust the magnification according to your shooting distance requirements.
- Use the parallax adjustment to ensure a clear image at your target distance.
- For windage and elevation adjustments, make precise clicks as indicated on the turret.

3. PostUse Care:

- Clean the lens with a soft, lintfree cloth to remove dust and fingerprints.
- Store the scope in a protective case when not in use to prevent damage.

Disposal Instructions

- **Environmental Responsibility:** Dispose of the product in accordance with local regulations regarding electronic waste.
- **NonUse:** If the product is no longer needed or is damaged beyond repair, contact a local waste disposal service for guidance on safe disposal.

Contact Information for Further Support

For any safety inquiries or support regarding the 5-25x56 PM II, please refer to the contact information provided by your retailer or manufacturer.

By adhering to these safety guidelines, you can ensure a safe and enjoyable experience with your 5-25x56 PM II scope. Thank you for your attention to these important safety measures.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk