

5-25x56 PM II - 5-25x56 PM II LP P4FL 1cm ccw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP P4FL 1cm ccw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015842
- Mfr. No.: 689-911-972-G8-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065435

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for the 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe use and handling of your product. Please read this document carefully before using the scope.

General Safety Guidelines

- **Product Safety:** This product is designed to be safe for use in accordance with EU regulations. Always follow the instructions provided in this guide to minimize risks.
- **Enhanced Recalls:** In case of safety concerns, recall notices will be issued promptly, and remedies will be provided free of charge for any dangerous products.
- **Online Shopping:** When purchasing online, ensure that the seller complies with EU safety requirements, similar to physical stores.
- **Special Consumer Focus:** Extra precautions apply to vulnerable groups, including children. Keep this product out of reach of children.
- **EU Contact Point:** For safety inquiries, please refer to the manufacturer's contact information provided with your product.
- **Rapid Alerts:** Stay informed about unsafe products through the EU's Safety Gate system, which provides timely updates.

Specific Safety Precautions for Use

- Always use the scope in accordance with the manufacturer's instructions.
- Do not use the scope for purposes other than those intended.
- Ensure the scope is securely mounted before use to avoid accidents.
- Avoid looking directly at the sun through the scope, as this can cause permanent eye damage.
- Use caution when adjusting the turrets and focusing the scope to prevent injury.
- Inspect the scope regularly for any signs of damage or wear. If damaged, discontinue use immediately.
- Store the scope in a dry, cool place when not in use to prevent moisture damage.

Instructions for Installation and Usage

Installation

1. **Select a Mounting Location:** Choose a stable and secure platform for mounting the scope.
2. **Attach the Scope:**
 - Use the appropriate rings and bases for your rifle.
 - Ensure the scope is level and aligned with the rifle.
3. **Secure the Mounting:** Tighten all screws and bolts securely but avoid overtightening, which may damage the scope or mounting hardware.

Usage

1. **Adjusting the Magnification:** Rotate the magnification ring to select the desired zoom level between 5x and 25x.
2. **Focusing the Scope:**
 - Adjust the focus by turning the eyepiece until the reticle appears sharp.
 - Use the parallax adjustment to focus the image based on the distance to the target.
3. **Using the Turret System:**
 - Make adjustments in clicks as specified (0.1 mrad or approximately 1 cm at 100 m).
 - For elevation, use the doubleturn turret for significant adjustments.
 - For windage, use the singleturn turret for finetuning.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic waste.
- Do not dispose of the product in regular household waste.
- If the product is damaged or no longer functional, consider recycling it at a designated facility.

Contact Information for Further Support

For any inquiries, concerns, or support regarding your 5-25x56 PM II, please refer to the contact information provided with your product.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk