

5-25x56 PM II - 5-25x56 PM II LP TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP TREMOR3 1cm ccw DT27 MTC LT / ST ZC CT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015845
- Mfr. No.: 689-911-552-G8-E8
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065398

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for the 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe use of this highquality tactical optic. Please read this guide carefully before using the product to familiarize yourself with the necessary safety precautions and operational guidelines.

General Safety Guidelines

- Ensure the product is used only for its intended purpose, which is longrange shooting and tactical applications.
- Always handle the optic with care to avoid damage.
- Regularly inspect the optic for any signs of wear or damage before use.
- Do not attempt to disassemble or modify the optic; doing so may void the warranty and compromise safety.
- Keep the optic out of reach of children and vulnerable individuals to prevent accidents.
- Store the optic in a dry and secure location when not in use.

Specific Safety Precautions for Use

- Always use the optic in a welllit environment to ensure optimal visibility.
- Adjust the parallax setting before use to ensure accurate focus at varying distances.
- Be aware of your surroundings and ensure a safe shooting environment.
- Use appropriate eye protection when using the optic to prevent injury.
- Check the turret settings before each use to ensure they are set correctly for your shooting conditions.
- If the optic becomes fogged or shows signs of moisture, discontinue use and allow it to dry completely before further use.
- Report any malfunction or irregularity to a qualified technician or authorized service center immediately.

Instructions for Installation and Usage

1. Installation:

- Mount the optic securely onto a compatible rifle using the appropriate rings or mounts.
- Ensure the main tube is level and aligned with the rifle's bore for optimal accuracy.
- Tighten the mounting screws to the manufacturer's recommended torque specifications.

2. Usage:

- Adjust the magnification by turning the magnification ring smoothly until the desired level is reached.
- Use the elevation and windage turrets to make necessary adjustments for bullet drop and windage.
- To focus the reticle, turn the eyepiece until the reticle appears sharp and clear.
- Always check the field of view and exit pupil before taking a shot to ensure proper alignment.

Disposal Instructions

- Dispose of the product in accordance with local regulations.
- Do not dispose of the product in regular household waste.
- If the product is beyond repair or no longer needed, consider recycling components where possible.

Contact Information for Further Support

For any safety inquiries or further support regarding the 5-25x56 PM II, please consult the authorized distributor or manufacturer.

Conclusion

By following these safety instructions, you can ensure a safe and enjoyable experience with your 5-25x56 PM II optic. Always prioritize safety and remain informed about best practices for the use of your equipment. Thank you for your attention to these guidelines.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk