

# 5-25x56 PM II - 5-25x56 PM II LP P5FL 1cm ccw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad ( $\approx 1$  cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×  
Objective Lens Diameter: 56 mm  
Main Tube Diameter: 34 mm  
Field of View: approx. 5.3-1.5 m @100 m  
Exit Pupil: approx. 11.0-2.3 mm  
Eye Relief: approx. 90 mm  
Parallax Adjustment: from ~10 m to infinity  
Click Value: approx. 0.1 mrad ( $\approx 1$  cm at 100 m)  
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

## Attributes

- Name: [5-25x56 PM II LP P5FL 1cm ccw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015847
- Mfr. No.: 689-911-622-L7-I5
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE  
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065602

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-25x56 PM II Scope](#)
- [About Us](#)

# Safety Instruction Guide for 5-25x56 PM II Scope

## Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This guide provides essential safety instructions and guidelines to ensure safe and effective use of your scope. Please read and follow these instructions carefully to maximize performance and minimize risks.

## General Safety Guidelines

- **Product Safety:** Ensure safe use of the scope by following the instructions provided. This product is designed for nonfood use and complies with relevant EU safety regulations.
- **Enhanced Recalls:** Stay informed about product recalls. In the event of a safety issue, standardized recall notices will be issued, and remedies will be provided free of charge.
- **Online Shopping:** If purchased online, know that you have the same safety protections as when buying in physical stores. Ensure that the platform meets safety requirements.
- **Special Consumer Focus:** Extra care should be taken when using this product around vulnerable groups, particularly children. Ensure they are supervised and kept at a safe distance during use.
- **EU Contact Point:** For safety inquiries, refer to the EU-based contact information provided by the retailer or manufacturer.
- **Rapid Alerts:** Stay updated on any safety alerts regarding the product through the EU's Safety Gate system.

## Specific Safety Precautions for Use

- **Avoid Eye Injuries:** Never look directly into the scope while it is pointed at a bright light source. Always use eye protection when necessary.
- **Proper Handling:** Handle the scope with care. Avoid dropping or subjecting it to strong impacts, as this may cause internal damage.
- **Moisture Protection:** Ensure the scope is kept dry and free from moisture. While it is fog and waterproof, prolonged exposure to water can still affect performance.
- **Temperature Extremes:** Avoid exposing the scope to extreme temperatures, as this may affect its components and performance.
- **Secure Mounting:** Ensure that the scope is securely mounted on the rifle. Regularly check the mounting to prevent loosening during use.
- **Use Appropriate Ammunition:** Always use ammunition that is compatible with the rifle and scope specifications to prevent damage and ensure safety.

## Instructions for Installation and Usage

- **Installation:**
  1. **Choose a Suitable Mount:** Select a mounting system compatible with the 34 mm main tube of the scope.
  2. **Secure the Mount:** Follow the manufacturer's instructions to securely attach the mount to your rifle.
  3. **Attach the Scope:** Carefully place the scope onto the mount and tighten it according to the specifications provided by the mount manufacturer.
  4. **Check Alignment:** Ensure that the scope is aligned properly for optimal performance.
- **Usage:**
  1. **Adjust Magnification:** Rotate the magnification ring to set the desired zoom level between 5x and 25x.

2. **Focus the Reticle:** Adjust the eyepiece focus until the reticle appears sharp and clear.
3. **Parallax Adjustment:** Use the parallax adjustment knob to set the focus based on the distance of your target, typically from 10 m to infinity.
4. **Elevation and Windage:** Use the turret system to adjust for elevation and windage. Click values are approximately 0.1 mrad ( $\approx 1$  cm at 100 m).

## Disposal Instructions

- **Environmental Responsibility:** Dispose of the scope and its packaging responsibly. Follow local regulations for electronic waste and hazardous materials.
- **Recycling:** If possible, recycle components of the scope to minimize environmental impact.

## Contact Information for Further Support

For any inquiries or concerns regarding the 5-25x56 PM II scope, please refer to the contact information provided by your retailer or the manufacturer. Always ensure that you have the latest safety information and updates.

By following these safety guidelines and instructions, you can ensure safe and effective use of your 5-25x56 PM II scope. Thank you for your attention to safety, and enjoy your shooting experience!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)