

5-25x56 PM II - 5-25x56 PM II LP TREMOR3 1cm ccw DT II+ MTC LT / ST II ZC LT

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP TREMOR3 1cm ccw DT II+ MTC LT / ST II ZC LT](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015849
- Mfr. No.: 689-911-552-L7-I5
- Colour: Black
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537033342

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your tactical optic. Please read this document carefully to understand how to use the product safely and responsibly.

General Safety Guidelines

- Ensure that the product is used only for its intended purpose.
- Keep the product out of reach of children and vulnerable individuals.
- Regularly inspect the product for any signs of damage or wear.
- Always follow the manufacturer's instructions for use and maintenance.
- Report any unsafe conditions or accidents to the appropriate authorities.
- Stay informed about product recalls and safety updates through the EU Safety Gate platform.

Specific Safety Precautions for Use

- **Eye Protection:** Always use appropriate eye protection when using the scope, especially during shooting activities.
- **Handling:** Handle the scope with care to avoid dropping or damaging it. Ensure that it is securely mounted to the rifle.
- **Weather Conditions:** Avoid using the scope in extreme weather conditions that could impair visibility or cause damage.
- **Adjustment Mechanisms:** Be cautious when adjusting the turrets and parallax settings. Make adjustments slowly and carefully to avoid misalignment.
- **Storage:** Store the scope in a dry, cool place when not in use. Use a protective case to prevent scratches and damage.

Instructions for Installation and Usage

1. Mounting the Scope:

- Select a suitable mounting base compatible with the 34 mm main tube diameter.
- Securely attach the scope to the rifle using the appropriate mounting rings.
- Ensure that the scope is level and properly aligned with the barrel.

2. Adjusting the Reticle:

- Use the elevation and windage turrets to zero the reticle at your desired distance.
- Make adjustments in small increments (0.1 mrad) for precision.

3. Focusing the Scope:

- Adjust the parallax setting to match the distance of your target (from ~10 m to infinity).
- Use the eyepiece focus to ensure a clear view of the reticle.

4. Using the Scope:

- When aiming, ensure a proper cheek weld for stability.
- Maintain a firm grip on the rifle and ensure your finger is off the trigger until ready to shoot.
- Always be aware of your surroundings and ensure a safe backdrop before firing.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic waste and optics.
- Remove batteries (if applicable) and recycle them separately at designated collection points.
- Do not dispose of the product in regular household waste.

Contact Information for Further Support

For any inquiries regarding safety or product issues, please consult local authorities or consumer protection agencies for guidance.

Thank you for your attention to these safety guidelines. Enjoy your experience with the 5-25x56 PM II, and remember to prioritize safety at all times.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk