

5-25x56 PM II - 5-25x56 PM II LP P5FL 1cm cw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP P5FL 1cm cw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015851
- Mfr. No.: 689-945-622-G9-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065756

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for the 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe and effective use of your product. Please read this document carefully before using the scope to understand how to operate it safely and responsibly.

General Safety Guidelines

- Always handle the scope with care to avoid damage.
- Do not look directly at the sun through the scope, as this may cause permanent eye damage.
- Ensure that the scope is securely mounted to your firearm before use.
- Use the scope only for its intended purpose, which is for precision shooting and tactical applications.
- Keep the scope out of reach of children and unauthorized users.
- Regularly inspect the scope for any signs of damage or wear. If any issues are found, discontinue use and seek professional assistance.
- Follow all local laws and regulations regarding the use of firearms and optical devices.

Specific Safety Precautions for Use

- **Magnification Adjustment:** Use caution when adjusting the magnification. Make sure to do so while the firearm is pointed in a safe direction.
- **Parallax Adjustment:** Ensure the parallax is adjusted correctly for the distance at which you are shooting to maintain accuracy and prevent misalignment.
- **Turret Adjustments:** Make adjustments to the windage and elevation turrets only when necessary, and ensure you are familiar with the click values to avoid overadjusting.
- **Weather Conditions:** Be aware of weather conditions that may affect visibility and safety. The scope is fog and waterproof; however, extreme temperatures may still impact performance.
- **Cleaning and Maintenance:** Use a soft, lintfree cloth to clean the lenses. Avoid using harsh chemicals or abrasive materials that could scratch the lens surface.

Instructions for Installation and Usage

1. Installation:

- Select a suitable mounting platform on your firearm that is compatible with a 34 mm main tube.
- Securely attach the scope to the firearm using appropriate mounting rings and ensure it is tight to prevent movement during use.
- Align the reticle with the bore of the firearm to ensure accurate shooting.

2. Usage:

- Adjust the magnification to your desired level based on the shooting distance.
- Focus the scope by adjusting the eyepiece until the reticle is sharp and clear.
- Set the parallax adjustment according to the distance you are shooting to maintain accuracy.
- Take aim and make any necessary adjustments to windage and elevation based on environmental conditions and target placement.
- Always follow safe shooting practices and ensure the firearm is pointed in a safe direction when not in use.

Disposal Instructions

- Dispose of the product in accordance with local regulations regarding electronic waste and optical devices.
- Do not dispose of the scope in regular household waste.
- Contact local waste management authorities for information on proper disposal methods.

Contact Information for Further Support

For any safety inquiries, please refer to your local regulations and guidelines. Ensure to follow all safety protocols and reach out to authorized professionals for assistance as needed.

Thank you for your attention to these safety instructions. Your safety and the safety of others is our priority. Enjoy your shooting experience with the 5-25x56 PM II scope responsibly.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk