

# 5-25x56 PM II - 5-25x56 PM II LP MSR2 1cm cw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad ( $\approx 1$  cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×  
Objective Lens Diameter: 56 mm  
Main Tube Diameter: 34 mm  
Field of View: approx. 5.3-1.5 m @100 m  
Exit Pupil: approx. 11.0-2.3 mm  
Eye Relief: approx. 90 mm  
Parallax Adjustment: from ~10 m to infinity  
Click Value: approx. 0.1 mrad ( $\approx 1$  cm at 100 m)  
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

## Attributes

- Name: [5-25x56 PM II LP MSR2 1cm cw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015852
- Mfr. No.: 689-945-812-G9-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE  
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065749

# Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for 5-25x56 PM II](#)
- [About Us](#)

# Safety Instruction Guide for 5-25x56 PM II

## Introduction

Thank you for choosing the 5-25x56 PM II from Schmidt and Bender. This guide provides essential safety instructions to ensure the safe use of your optical device. Please read this guide carefully before using the product.

## General Safety Guidelines

- Ensure that the product is used according to the manufacturer's instructions.
- Always handle the scope with care to avoid physical damage.
- Do not expose the product to extreme temperatures or moisture beyond its specifications.
- Keep the product out of reach of children and vulnerable individuals to prevent accidents.
- Regularly inspect the scope for any signs of damage or wear. If you notice any issues, cease use immediately.
- Report any unsafe product experiences or accidents to the relevant authorities.

## Specific Safety Precautions for Use

- Always use the scope in a safe environment, free from distractions and hazards.
- When adjusting the scope, ensure that it is securely mounted to avoid unintentional movement.
- Do not look directly at the sun through the scope, as this can cause serious eye damage.
- Ensure that all adjustments (e.g., parallax, elevation, windage) are correctly set before use.
- Understand the limitations of the scope and do not exceed the specified ranges for optimal performance.

## Instructions for Installation and Usage

### 1. Installation:

- Mount the scope securely onto a compatible rifle using the appropriate mounting rings and bases.
- Ensure that the main tube is level and aligned with the rifle's barrel.
- Tighten all screws and mounts according to the manufacturer's specifications to prevent movement during use.

### 2. Usage:

- Before using the scope, familiarize yourself with all controls and adjustments.
- Adjust the magnification according to your needs by rotating the magnification ring.
- Use the parallax adjustment to ensure a clear image at your shooting distance.
- Check the eye relief and adjust your shooting position to maintain comfort and safety.
- Always ensure that the area is clear of people and obstacles before taking a shot.

## Disposal Instructions

- Dispose of the product in accordance with local regulations for electronic waste.
- Do not dispose of the product in regular household waste.
- If the product is damaged, consult local disposal facilities for safe handling and recycling options.

## Contact Information for Further Support

For any questions or concerns regarding the product, please refer to the manufacturer's website or customer service for assistance. Ensure you have your product details ready for a more efficient response.

By following these safety instructions, you can ensure a safe and enjoyable experience with your 5-25x56 PM II scope. Thank you for prioritizing safety!

# About Us

## Brownells UK

### **Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories**

Unit 1, Laughing Dog Industrial Estate  
London Road  
Rugby  
Warwickshire  
CV23 9LP

[www.brownells.co.uk](http://www.brownells.co.uk)