

5-25x56 PM II - 5-25x56 PM II LP TREMOR3 1cm cw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP TREMOR3 1cm cw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015853
- Mfr. No.: 689-945-552-G9-E9
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065725

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II Scope](#)
- [About Us](#)

Safety Instruction Guide for the 5-25x56 PM II Scope

Introduction

Thank you for choosing the 5-25x56 PM II Scope from Schmidt and Bender. This guide provides essential safety instructions to ensure safe and effective use of your product. It is important to read and understand these instructions before using the scope.

General Safety Guidelines

- **Product Safety:** The 5-25x56 PM II Scope is designed for safe use. Always follow the instructions provided to minimize risks.
- **Enhanced Recalls:** In the event of a safety issue, standardized recall notices will be issued. Stay informed about any recalls related to your product.
- **Online Shopping:** If purchased online, ensure that the seller complies with safety regulations. You have the same rights as when purchasing in a physical store.
- **Special Consumer Focus:** This product is not intended for children. Always supervise use around minors.
- **EU Contact Point:** For any safety inquiries, please contact the designated EU representative.
- **Rapid Alerts:** Stay updated on product safety by checking the EU's Safety Gate platform for any alerts related to this scope.

Specific Safety Precautions for Use

- **Eye Protection:** Always wear appropriate eye protection when using the scope to prevent injury.
- **Handling:** Handle the scope with care. Avoid dropping or knocking it against hard surfaces.
- **Moisture:** Do not expose the scope to excessive moisture. It is nitrogenfilled and fogproof, but prolonged exposure to water can damage internal components.
- **Temperature:** Avoid using the scope in extreme temperatures. It is designed for a range of conditions, but extreme heat or cold can affect performance.
- **Mounting:** Ensure that the scope is securely mounted to your firearm. A loose scope can lead to inaccurate shooting and potential accidents.
- **Maintenance:** Regularly check the scope for signs of wear or damage. If any issues are found, discontinue use and seek professional assistance.

Instructions for Installation and Usage

1. Installation:

- Select a mounting location on your firearm that is suitable for your shooting style.
- Use appropriate mounting rings compatible with the 34 mm main tube diameter.
- Securely tighten the mounting rings to ensure the scope does not move during use.
- Ensure the scope is level before tightening fully.

2. Usage:

- Before using the scope, familiarize yourself with its features, including magnification settings and turret adjustments.
- Adjust the magnification by rotating the zoom ring smoothly to your desired level.
- Use the parallax adjustment to focus on your target accurately. Set it from 10 m to infinity depending on your shooting distance.
- When adjusting the turrets, make sure to count clicks for accurate adjustments.

- Always check the field of view and exit pupil to ensure proper alignment with your eye.

Disposal Instructions

- Dispose of the scope in accordance with local regulations. Do not dispose of it in regular household waste.
- If the scope is damaged or no longer functional, consider recycling components where possible.
- Contact local waste management authorities for guidance on proper disposal methods.

Contact Information for Further Support

For any questions or concerns regarding the safety and functionality of your 5-25x56 PM II Scope, please refer to the designated EU representative for assistance.

By following these safety instructions, you can ensure a safe and enjoyable experience with your 5-25x56 PM II Scope. Always prioritize safety and responsible usage.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk