

5-25x56 PM II - 5-25x56 PM II LP P4FL 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000

[Optics & Mounting](#) > [Scopes](#) > [Rifle Scopes](#)

The 5-25×56 PM II from Schmidt and Bender stands at the pinnacle of variable-magnification tactical optics, engineered for long-range precision, outstanding clarity and professional-level reliability. With a wide 5-25× zoom range and a substantial 56 mm objective lens, it delivers exceptional light-gathering capability, enabling crisp, bright imagery even at extended distances.

Built upon a rugged 34 mm main tube, the scope accommodates large internal adjustment ranges and is designed for demanding use. It features a reticle in the first focal plane (FFP) so that scale and hold-offs remain accurate at any magnification. The field of view spans approximately 5.3-1.5 m at 100 m, while the exit pupil ranges around 11.0-2.3 mm, and the eye relief remains generous at around 90 mm. The parallax adjustment typically extends from 10 m to infinity, enabling accurate focus from very close ranges through to extreme distances.

The turret system is engineered for precision: click values as fine as 0.1 mrad (≈ 1 cm at 100 m) are available, and a double-turn elevation turret combined with single-turn windage allows vast usable correction ranges for wind and elevation. Optical transmission exceeds 90 %, and the construction is nitrogen-filled, fog- and waterproof, ensuring full reliability in all climatic conditions.

Key Specifications:

Magnification: 5-25×
Objective Lens Diameter: 56 mm
Main Tube Diameter: 34 mm
Field of View: approx. 5.3-1.5 m @100 m
Exit Pupil: approx. 11.0-2.3 mm
Eye Relief: approx. 90 mm
Parallax Adjustment: from ~10 m to infinity
Click Value: approx. 0.1 mrad (≈ 1 cm at 100 m)
Optical Transmission: > 90 %

Crafted in Germany to the highest standards, the 5-25×56 PM II is the go-to choice for military, law-enforcement and competition shooters who demand absolute clarity, mechanical integrity and extreme flexibility in one optic.

Attributes

- Name: [5-25x56 PM II LP P4FL 1cm ccw DT27 MTC LT / ST ZC CT RAL 8000](#)
- Manufacturer: [SCHMIDT U. BENDER](#)
- Product no.: EU2015854
- Mfr. No.: 689-945-972-G8-E8
- Colour: FDE
- Delivery weight: 2kg
- Shipping height: 100mm
- Shipping width: 100mm

NO IMAGE
AVAILABLE

- Shipping length: 450mm
- EAN: 4060537065695

Table of Contents

- [Startpage](#)
- [Safety Instruction Guide for the 5-25x56 PM II](#)
- [About Us](#)

Safety Instruction Guide for the 5-25x56 PM II

Introduction

Thank you for choosing the 5-25x56 PM II scope from Schmidt and Bender. This guide provides essential safety instructions to ensure your safe use of this product. Please read and follow the guidelines carefully to maximize your safety and the performance of your scope.

General Safety Guidelines

- **Product Safety:** Ensure safe usage of the scope by following all provided instructions. The scope is designed for tactical optics and should be used in accordance with its specifications.
- **Enhanced Recalls:** Be aware that in the event of a product recall, standardized notices will be issued. Always check for updates regarding your product.
- **Online Shopping:** If purchased online, ensure that the seller complies with EU safety requirements.
- **Special Consumer Focus:** Extra caution should be exercised if the product is used by vulnerable groups, including children. The scope is not a toy and should be kept out of reach of children.
- **EU Contact Point:** For safety inquiries, refer to the relevant EU contact points provided by the manufacturer.
- **Rapid Alerts:** Stay informed about any safety alerts or recalls through the EU's Safety Gate platform.

Specific Safety Precautions for Use

- **Avoid Eye Injury:** Always use protective eyewear when using the scope to prevent eye injury from recoil or other hazards.
- **Proper Handling:** Handle the scope with care. Avoid dropping or subjecting it to sudden impacts.
- **Environmental Conditions:** Do not use the scope in extreme weather conditions beyond its specifications, such as heavy rain or extreme heat.
- **Mounting:** Ensure that the scope is securely mounted on the rifle to avoid accidents during use.
- **Cleaning:** Use only recommended cleaning materials to maintain the lens and body integrity. Avoid abrasive materials.
- **Storage:** Store the scope in a cool, dry place when not in use to prevent damage from humidity or temperature fluctuations.
- **Child Safety:** Keep the scope out of reach of children. It is not designed for use by individuals under the age of 18.

Instructions for Installation and Usage

- **Installation:**
 1. **Mounting the Scope:** Use a compatible mounting system designed for a 34 mm main tube.
 2. **Leveling:** Ensure the scope is level before tightening the mounting rings.
 3. **Secure Fastening:** Tighten the mounting screws according to the manufacturer's specifications to prevent movement during use.
- **Usage:**
 1. **Adjusting Magnification:** Rotate the magnification ring to select the desired zoom level (5-25x).
 2. **Parallax Adjustment:** Use the parallax adjustment feature to focus on the target at the appropriate distance, ranging from ~10 m to infinity.
 3. **Elevation and Windage:** Adjust the turret system for elevation and windage. Each click is approximately 0.1 mrad (≈ 1 cm at 100 m).
 4. **Field of View:** Be aware that the field of view spans approximately 5.3-1.5 m at 100 m.
 5. **Exit Pupil and Eye Relief:** Ensure your eye is positioned correctly to utilize the exit pupil (approx.

11.0–2.3 mm) and maintain the generous eye relief of around 90 mm.

Disposal Instructions

- **Environmental Responsibility:** Dispose of the scope in accordance with local regulations for electronic waste and materials.
- **Recycling:** If possible, recycle components of the scope, such as the metal and glass, at designated recycling facilities.
- **Hazardous Materials:** If the scope contains any hazardous materials, follow specific disposal guidelines to prevent environmental contamination.

Contact Information for Further Support

For any questions or concerns regarding the 5–25x56 PM II scope, please refer to the contact information provided by the manufacturer or retailer from whom you purchased the product. They will be able to assist you with any safety inquiries or technical support.

Thank you for your attention to these safety guidelines. Enjoy using your 5–25x56 PM II scope responsibly and safely.

About Us

Brownells UK

Brownells UK - World's Largest Supplier of Gun Parts, Gunsmith Tools & Shooting Accessories

Unit 1, Laughing Dog Industrial Estate
London Road
Rugby
Warwickshire
CV23 9LP

www.brownells.co.uk